

PRODUCT-DETAILS

RB122G-48-60VUC

RB122G-48-60VUC Interface relay R600

2c/o,A1-A2=48-60VAC/DC,5-250VAC/10mA-8A



Algemene informatie

Type	RB122G-48-60VUC
Artikelnummer	1SNA645040R1500
EAN	4013614508004
Omschrijving	RB122G-48-60VUC Interface relay R600 2c/o,A1-A2=48-60VAC/DC,5-250VAC/10mA-8A

Omschrijving

The RB122G-48-60VUC is a boxed interface relay with screw terminals, which can be seamlessly snap-on mounted onto a DIN Rail. The relay is soldered into device housing, ensuring a high resistance against vibration. This relay operates with a 48-60 V AC/DC rated control supply voltage and has a 2 c/o (SPDT) output with gold-plated contacts rated at 250 V / 8 A. This 12mm wide boxed interface relay may be used for electrical isolation, amplification and signal matching and enables the switching of high currents on a small footprint. It has an integrated LED, which provides the visual indication of the energization of the relay coil and UL 94-V0 certified device housing, improving safety by providing high levels flame retardation. Jumper bars are available as accessories.

Ordering

EAN	4013614508004
Minimale bestelhoeveelheid	5 stuk
Nummer douanetarief	85364900

Popular Downloads

Gegevensblad, technische informatie	2CDC110004C0210_05
Instructies en handleidingen	1SVC645000M9000
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product netto breedte	12 mm
Product netto hoogte	67.5 mm
Product netto diepte	70 mm
Product netto gewicht	0.04 kg

Technical

Functie	Interfacerelais R600 in doos
Subfunctie	Relay with built in LED
Nominaal stuurvoltage (U _s)	48 ... 60 V AC/DC
Uitgang	2 c/o (SPDT) contacts
Uitgangssignaal	5 ... 250VAC / 10mA ... 8A
Terminaltype	Schroef
Beschermingsgraad	IP20
Normen	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60947-5-1 UL 508

Environmental

RoHS-status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations

CB-certificaat	CB_DK-53188-UL
CCC-certificaat	CCC_2017010303941444
CQC-certificaat	CQC_2017010303941444
CSA-certificaat	CSA_254821
cUR-certificaat	cUR_E352056
Declaration of Conformity - CCC	CCC_2020980303000254
Conformiteitsverklaring - CE	1SVD982016-0001
Declaration of Conformity - UKCA	1SVD982016-1000
EAC-certificaat	EAC_RU_C-FR.ME77.B.01634
LR-certificaat	LR_16_20068
UR-certificaat	UR_E352056

Container Information

Pakketniveau 1 Units	doos 5 stuk
Pakketniveau 1 Breedte	73 mm
Pakketniveau 1 Lengte	80 mm

Pakketniveau 1 Hoogte	71 mm
Pakketniveau 1 Brutogewicht	0.24 kg
Pakketniveau 1 EAN	3472596450403

Classifications

Object classificatiecode	K
ETIM 7	EC001437 - Switching relay
ETIM 8	EC001437 - Schakelrelais
ETIM 9	EC001437 - Schakelrelais
eClass	V11.0 : 27371601
UNSPSC	39122331

Categorieën

Laagspanningsproducten en -systemen → Control Producten → Elektronisch relais en bediening → Interfacerelais en optokoppelaars

