



LED luminaire MONA 2, with a power of 27 W. It is made of high-quality components, supported by a 5-year warranty. Narrow beam angle 36° gives directional light so that selected objects or surfaces can be better exposed. Designed for recessed mounting.





Power	27 W	Voltage	230 V
Colour of light	MEAT	Beam angle	36 °
Degree of protection (IP)	IP20		

www.spectrumled.pl



Technical data

Code	W0JP05542		
Power	27 W		
Nominal current	129 mA		
Voltaae	230 V		
Energy consumption	27 kWh/1000h		
Frequency	50HZ Hz		
Protection class			
Power supply included	+		
Manufacturer of power	BOKE		
supply	DUKL		
Power factor	0.93		
Useful luminous flux*	2295 lm (360°)		
Luminous flux**	1890 lm (360°)		
Lamp efficacy	85 lm/W		
Colour of light	MEAT		
Beam angle	36 °		
RA	80		
Light source included	+		
Producer of LED diodes	CITIZEN		
Uniformity of color SDCM max	3		
Dimmable	1-10V		
Working temperature range	-20/+40 °		
Lifespan	50000 h		
Housing material	Aluminum		
Degree of protection (IP)	IP20		
Colour	White		
Dimension (AxBxC)	142x118 mm		
Mounting hole	0110 mm		
For use	Inside		
Assembly method	Recessed		
Application	Inside		
Made in	PL		

Related documents



3D model