

PRODUCT-DETAILS

S401M-B40

S401M-B40 Miniature Circuit Breaker



Algemene informatie

Type	S401M-B40
Artikelnummer	2CCS571001R0405
EAN	7612270101290
Omschrijving	S401M-B40 Miniature Circuit Breaker

Omschrijving

SMISSLINE TP S400M are a current limiting miniature circuit breakers. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K), configurations (1P,1P+N,2P,3P,3P+N), breaking capacities (up to 10 kA at 240/415 V AC) and rated currents (up to 63A). MCBs of the product range S400M are comply with IEC/EN 60898-1 for B,C and D characteristic and IEC/EN 60947-2 for C and K characteristic. The pluggable solution is only for the SMISSLINE TP System, allowing the use for commercial, industrial, and critical power applications.

Technical

Normen	IEC/EN 60898-1
Uitschakelkenmerk	B
Nominaal bedrijfsvoltage	acc. to IEC 60898-1 230 V AC
Operationeel voltage	Minimum 12 V AC
Nominaal isolatievoltage (U _i)	acc. to IEC/EN 60664-1 440 V

Nominale impuls grensvoltage (U_{imp})	4 kV
Ingangsspanningstype	AC
Toegekende stroom (I_n)	40 A
Nominale bedrijfsstroom (I_e)	40 A
Nominaal kortsluitvermogen	(AC) 10 kA (230 / 400 V AC) 10 kA
Frequentie (f)	50 ... 60 Hz
Toegekende frequentie (f)	50 ... 60 Hz
Vermogensverlies	3.7 W
Aansluiting voeding	Arbitrary
Statusindicator	Red ON / Green OFF
Energiebeperkende klasse	3
Elektrisch uithoudingsvermogen	10000 cycle
Mechanisch uithoudingsvermogen	10000 cycle
Aantal polen	1
Aantal beveiligde polen	1
Overspanningscategorie	III
Aanhaalmoment	2.8 N·m
Uitgavetype	B
Type schroefklem	Failsafe Bi-directional Cylinder-lift Terminal
Aansturingsmarkering	I / O
Plaats van inbouw	Any
Aanbevolen schroevendraaier	Pozidriv 2
Accessoires beschikbaar	Yes
Verbindingscapaciteit	Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ² Stranded 0.75 ... 35 mm ²
Terminaltype	Schroef

Environmental

Omgevingsluchttemperatu ur	Werking -25 ... +60 °C Opslag -40 ... +70 °C
Referentie omgevingsluchttemperatu ur	30 °C
Beschermingsgraad	IP20
Verontreinigingsgraad	3
Weerstand tegen trillingen volgens IEC 60068-2-6	2...13.2 Hz/1 mm 13.2...100Hz/0.7 g, 5 cycles 5...150 ... 5 Hz/1 g, 4 waves
RoHS-status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS-informatie	9AKK107991A9634

Milieu-informatie	9AKK108467A9561
Rapport over conflictmineralen (CMRT)	9AKK108468A3363

Dimensions

Breedte in module- eenheden	1
Product netto breedte	18 mm
Product netto hoogte	91 mm
Product netto diepte	75 mm
Product netto gewicht	110 g
Grootte	1 module
Inbouwdiepte (t ₂)	75 mm
Dimensiediagram	9AKK107492A6192

Ordering

Minimale bestelhoeveelheid	1 stuk
Pakketniveau 1 Units	karton 10 stuk
Pakketniveau 1 Brutogewicht	1165 g
E-Number (Switzerland)	809023807

Certificates and Declarations

Conformiteitsverklaring - CE	9AKK107991A9634
---------------------------------	-----------------

Installation

Instructies en handleidingen	2CCC451019M0109
---------------------------------	-----------------

Popular Downloads

Gegevensblad, technische informatie	9AKK107492A6192
--	-----------------

Classifications

ETIM 8	EC000042 - Installatieautomaat
ETIM 9	EC000042 - Installatieautomaat
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
AEEA B2C / B2B	Business To Business
CN8	85362020
eClass	V11.0 : 27141901

Object classificatiecode FC

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CCS500900R0081	HK40011-L Auxiliary swtich	HK40011-L	1	piece
2CCS500900R0214	HK40011-R Auxiliary swtich	HK40011-R	1	piece
2CCF201112R0001	HK40020-L Auxiliary swtich	HK40020-L	1	piece
2CCF201114R0001	HK40002-L Auxiliary swtich	HK40002-L	1	piece
2CCF201113R0001	HK40020-R Auxiliary swtich	HK40020-R	1	piece
2CCF201115R0001	HK40002-R Auxiliary swtich	HK40002-R	1	piece
2CCS500900R0101	SK40011-L Signal contact	SK40011-L	1	piece
2CCS500900R0215	SK40011-R Signal contact	SK40011-R	1	piece
2CCF201162R0001	SK40020-L Signal contact	SK40020-L	1	piece
2CCF201164R0001	SK40002-L Signal contact	SK40002-L	1	piece
2CCF201163R0001	SK40020-R Signal contact	SK40020-R	1	piece
2CCF201165R0001	SK40002-R Signal contact	SK40002-R	1	piece
2CCS500900R0141	SK40010-LSA Signal contact	SK40010-LSA	1	piece
2CCF201212R0001	HK400 10-L SA Auxiliary swtich	HK40010-LSA	1	piece
2CCS500900R0216	SK40010-RSA Signal contact	SK40010-RSA	1	piece
2CCF201213R0001	HK400 10-R SA Auxiliary swtich	HK40010-RSA	1	piece
2CCS500900R0161	ZLS931 Spare parts	ZLS931	1	piece
2CCS500900R0021	NT401-63 Neutral disconnect terminal block	NT40163	1	piece
2CCS500900R0011	NT402-63 Neutral disconnect terminal block	NT40263	1	piece
2CDS200909R0001	S2C-A1 Shunt Trip	S2C-A1	1	piece
2CDS200909R0002	S2C-A2 Shunt Trip	S2C-A2	1	piece
2CCA880211R0001	CMS-121PS Sensor	CMS-121PS	1	piece
2CCA880101R0001	CMS-101PS Sensor	CMS-101PS	1	piece

Categorieën

Laagspanningsproducten en -systemen → Modulaire DIN rail producten → Plug-in Distribution Systems → Plug-in stroomverdeling → Miniature Circuit Breakers MCBs

