



CorePro LEDcapsule LV



CorePro LEDcapsuleLV 2.1-20W G4 827 D

The CorePro LEDcapsule is a true alternative to the halogen capsule. It is particularly suitable for task lighting and decorative applications in homes, shops, hotels and restaurants. Compatible with existing fixtures with G4 holders and designed for retrofit replacement of halogen capsules, CorePro LEDcapsule delivers huge energy savings and minimizes maintenance costs without any compromise on light quality.

Product data

General Information	
Cap-Base	G4
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	827 [CCT of 2700K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	210 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	100.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 6247	1 RG1

Operating and Electrical	
Line Frequency	- Hz
Input Frequency	- Hz
Power Consumption	2.1 W
Lamp Current (Nom)	210 mA
Wattage Equivalent	20 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (Nom)	ac electronic 12 V
Temperature	
T-Case Maximum (Nom)	80 ℃
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb Shape	Capsule


Datasheet, 2025, January 10 data subject to change

CorePro LEDcapsule LV

Net Weight (Piece)	0.010 kg
Approval and Application	
Energy Efficiency Class	F
Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	3 kWh
EPREL Registration Number	374870
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Application Conditions	
can it be used in closed luminaires	No


Product Data	
Order product name	CorePro LEDcapsuleLV 2.1-20W G4 827 D
Full product name	CorePro LEDcapsuleLV 2.1-20W G4 827 D
Full product code	871869976753200
Order code	929002389402
Material Nr. (12NC)	929002389402
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699767532
Numerator - Packs per outer box	12
EAN/UPC - Case	8718699767549


Dimensional drawing



Product	D	С
CorePro LEDcapsuleLV 2.1-20W G4 827 D	15 mm	40 mm

Photometric data





180°


150°

Spectral Power Distribution Colour - CorePro LEDcapsuleLV 2.1-20W G4 827 D

Light Distribution Diagram - CorePro LEDcapsuleLV 2.1-20W G4 827 D

CorePro LEDcapsule LV


Photometric data




Calculus Photometrics 4.5 Philips Lighting Scv. Fagor 1H

General uniform lighting - CorePro LEDcapsuleLV 2.1-20W G4 827 D

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - CorePro LEDcapsuleLV 2.1-20W G4 827 D



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.