


PRODUCT-DETAILS

# OT160EV03P

## OT160EV03P SWITCH-DISCONNECTOR



### General Information

Extended Product Type	OT160EV03P
Product ID	1SCA120514R1001
EAN	6417019519746
Catalog Description	OT160EV03P SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, base mounted switch-diconnector with black IP65 handle and shaft, terminal bolt kit included

### Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Environmental Information	1SCC301265D0201
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Country of Origin	Finland (FI)
-------------------	--------------

## Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301031M0220
Mechanical Drawings	1SCC307633F0001 1SCC307632F0001 OT200-250E03.stp OT200-250E03.igs

## Dimensions

Product Net Width	150 mm
Product Net Height	145.5 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	1.3 kg

## Technical

Rated Operational Current AC-21A ( $I_g$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A (1000 V) 200 A
Rated Operational Current AC-22A ( $I_g$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 160 A
Rated Operational Current AC-23A ( $I_g$ )	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Power AC-23A ( $P_g$ )	(220 ... 240 V) 48 kW (400 ... 415 V) 88 kW (500 V) 112 kW (690 V) 144 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	$\Theta = 40^\circ\text{C}$ 200 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 160 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V) 30 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 8 kA
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(315 A fuse, 500 V) 100 kA (355 A fuse, 690 V) 80 kA (250 A fuse, 690 V) 100 kA

Power Loss	at Rated Operating Conditions per Pole 3.2 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism at the End of the Switch 03 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 15 ... 22 N·m
Mechanical Durability	20000
Lock Type	Yes

## Technical UL/CSA

Tightening Torque	acc. IEC 60947-1 15 ... 22 N·m
-------------------	--------------------------------

## Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	1SCC301265D0201

## Certificates and Declarations

ATEX Certificate	No certification needed
Declaration of Conformity - CE	1SCC301131D2705
DNV GL Certificate	1SCC301174D0204
REACH Declaration	1SCC011021D0201
UL Certificate	No certification needed
VDE Certificate	No certification needed

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	170 mm 6.7 in
Package Level 1 Depth / Length	190 mm 7.5 in
Package Level 1 Height	145 mm

---

	5.7 in
Package Level 1 Gross Weight	1.5 kg 3.2 lb
Package Level 1 EAN	6417019519746

---

## Classifications

---

Object Classification Code	Q
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601362
E-Number (Sweden)	3170908

---

## Categories

---

Low Voltage Products and Systems → Switches → Switch Disconnectors

