


# Pace Backlit 1200x600 Panel



- Backlit LED panel suitable for education, commercial and ancillary area applications
- Slimline design allows for installation into shallow ceiling voids
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Cool white, warm white and daylight options
- Self-Test Panel Pod and Sensor Pod compatible
- Dimmable and OCTO options available
- TPa as standard
- Powered by Tridonic
- **Self-Test Panel Pod and Sensor Pod compatible (see p522 for more information)**



Panel Pod  
Emergency installed



Powered by  
**CASAMBI**



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220-240V	50-60Hz	-10°C to 40°C	L80 54,000	Ra 80	3	85°	2	IP44

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR	TRADE
APACLED1/120/WW	1200 x 600 - Cool White	46W	3000K	5300lm	115lm	17	£152.00
APACLED1/120/CW	1200 x 600 - Warm White	46W	4000K	5500lm	120lm	17	£152.00
APACLED1/120/DL	1200 x 600 - Daylight	46W	6500K	5500lm	120lm	17	£152.00

AIRMLED/POD/3NM/ST	Emergency Pod	5W					£112.00
AIRMLED/POD/MWS	Sensor Pod	1W					£73.00

\* UGR Value based on (4H - 8H)

CODE (OPTIONS)	DESCRIPTION	TRADE
/DM3	DALI Emergency	+ £205.00
/OCTO	OCTO Smart Control	+ £195.00
/DD	Digital Dimming (DD1/DD3/DD4)	+ £95.00

CODE (ACCESSORIES)	DESCRIPTION	TRADE
APACLED/SK	Pace Suspension Kit	£12.75
AERMLED/120/SMF	1200x600 Surface Mounting Frame	£61.50
APRK/120	1200x600 Plasterboard Recessed Kit	£101.00