

# ALGINE BACKLIGHT

SLI035063NW\_PW

LED panel ALGINE BACKLIGHT, with a power of 64 W, high light efficacy 128 lm/W. It is made of high-quality components, supported by a 5-year warranty. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Designed for recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	<b>64 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>8200 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>120 °</b>
UGR	<b>&lt;19</b>	Degree of protection (IP)	<b>IP20</b>

## Technical data


---

Code	SLI035063NW_PW
Power	64 W
Nominal current	280 mA
Voltage	230 V
Energy consumption	64 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	8200 lm (360°)
Luminous flux**	7500 lm (360°)
Lamp efficacy	128 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
UGR	<19
RA	>80
Uniformity of color SDCM max	5
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x1195x37 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC

## Related documents

---



 Declaration of Conformity



 Photometric file

