

## ASPS 110 420 L (767 571)

- Insulating stick with plug-in coupling as end fitting for extending the handle
- In a suitable storage bag



Figure without obligation

Figure without obligation

### Parts list:

Pos.	Part No.	Pos.	Part No.
1	767 576	6	767 564
2	767 577	7	766 369
3	767 591	8	767 574
4	767 592	9	767 996
5	767 593		

For more detailed information on these products, see Accessories chapter.

Type	ASPS 110 420 L
Part No.	767 571
Nominal voltage (U <sub>N</sub> )	110 ... 420 kV
Type of voltage	a.c.
Frequency	50 Hz
Total length (l <sub>Δ</sub> )	960 mm
Category	L
Temperature range	-25 °C ... +55 °C
For use at	▲
For	Overhead lines and outdoor switching stations
Application	Overhead lines
Design	Single-pole
Indication	Acoustic and visual
Self-testing element	Yes
Material (indicator)	Plastic, fully insulated (black)
Material (electric field sensor)	Plastic (black)
Material (insulating stick)	Glass-fibre reinforced polyester tube
Weight	1,99 kg
Customs tariff number	90303370
GTIN	4013364124967
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.