

ORBITO

SLI043020NW_PW

See
more

LED luminaire ORBITO, with power regulation on the power supply (14-27 W), high light efficacy 120 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a high IP44 rating, making it ideal for use in rooms with high humidity. It also stands out for its very high colour rendering index RA>90. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Narrow beam angle 40° gives directional light so that selected objects or surfaces can be better exposed. Designed for recessed mounting.




Power	14-27 W	Voltage	230 V
Colour temperature	4000 K	Colour of light	Neutral white
Beam angle	40 °	UGR	<19
IK	06	Degree of protection (IP)	IP44

Technical data

Code	SLI043020NW_PW
Power	14-27 W
Nominal current	125 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	3250 lm (360°)
Luminous flux**	1300-2600 lm (360°)
Lamp efficacy	120 lm/W
Luminous intensity	4000 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	40 °
UGR	<19
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
IK	06
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	169x95 mm
Mounting hole	140 mm
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

Related documents

 User manual Declaration of Conformity Photometric file 3D model

