


61794951	DATA SHEET	
Valid from: 20.01.2022	Panel connectors insulated (Type V)	

Insulated panel connectors for fine wire cables.

Material:

Body Copper, tinned
Coat Polyamide



Technical features:

For cross section 0,5mm² up to 6mm²
Temperature range -20°C up to +105°C

Additional features:

Fire classification V2 acc. to UL94

Color:

Red
Blue
Yellow

Approvals:



E334111

Suitable glands:

PEW 12 Universal tool
Crimping insert PEW 12.060

Dimension table:

Part No.	For mm ²	UL Certificates	Color	Blade injection	d mm	L mm	W mm
61794951	0,5 – 1,5	Yes	Red	2,8 x 0,5	3,8	19,3	5,0
61794952	0,5 – 1,5	Yes	Red	2,8 x 0,8	3,8	19,3	5,0
61794953	0,5 – 1,5	Yes	Red	4,8 x 0,5	3,6	20,2	7,4
61794955	0,5 – 1,5	Yes	Red	4,8 x 0,8	3,6	20,2	7,4
61794960	0,5 – 1,5	Yes	Red	6,3 x 0,8	4,4	21,0	8,8
61794969	1,5 – 2,5	Yes	Blue	4,8 x 0,8	4,3	20,0	7,4
61794970	1,5 – 2,5	Yes	Blue	6,3 x 0,8	4,5	21,0	8,8
61794971	4,0 – 6,0	Yes	Yellow	6,3 x 0,8	5,3	26,0	9,0

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: MAU1/PDP Released: DAMU1/PDP	Document: DB61794951EN Version: 00	Page 1 of 1
--	---------------------------------------	-------------