

LIMEA CONNECT

SLI028110NW_PW

Hermetic luminaire LIMEA CONNECT, with a power of 25 W, high light efficacy 160 lm/W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



| | | | |
|-----------------|-----------------------|---------------------------|---------------|
| Power | 25 W | Voltage | 230 V |
| Luminous flux* | 4000 lm (360°) | Colour temperature | 4000 K |
| Colour of light | Neutral white | Beam angle | 120 ° |
| IK | 08 | Degree of protection (IP) | IP65 |

Technical data


| | |
|------------------------------|---------------------------|
| Code | SLI028110NW_PW |
| Power | 25 W |
| Nominal current | 115 mA |
| Voltage | 230 V |
| Energy consumption | 25 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Power factor | 0.96 |
| Useful luminous flux* | 4000 lm (360°) |
| Luminous flux** | 3000 lm (360°) |
| Lamp efficacy | 160 lm/W |
| Colour temperature | 4000 K |
| Colour of light | Neutral white |
| Beam angle | 120 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 26000 h |
| Housing material | PC/PC |
| IK | 08 |
| Degree of protection (IP) | IP65 |
| Colour | Gray |
| Dimension (AxBxC) | 600x64x60 mm |
| For use | Inside/Outside |
| Assembly method | On the ceiling, Suspended |
| Application | INT/EXT |
| Made in | PRC |
| Other | MAX 22 pcs per line , |

Related documents



 User manual



 Declaration of Conformity



 Photometric file

