### **Product Data Sheet**

# GW68242N

#### 68 ACS Range




Mobile, transportable terminal boards Type 68 Q-DIN are especially suitable for powering mobile tools and equipment. The accessories - including handles, floor-mounting supports and wheeled carriages - make it extremely easy to move the boards around the site. The 68 Q-DIN ACS boards are available in various configurations with interlocked or fixed IEC 309 socket-outlets in both the protected and watertight versions. Each board comes complete with cable and relative mobile plug for powering portable devices everywhere. The boards can also be equipped with safety locks with a metallic cylinder, and can be mounted on poles or walls, or on mobile floor-mounting supports.

Туре	Q-DIN 5 ACS	board type	Wired		
Outer dim. LxHxD (mm)	105x430x96	Weight (kg)	4		
Accordance with Standards	EN 61439-4 (ACS)	Characteristics	UV resistance (EN 62208)		
IP degree	IP65	Mechanical resistance	IK09		
Glow wire test	650 °C	Thermo-pressure with ball	70 °C		
Insulation class	II	Power supply	Mobile plug		
No. of poles	3P+N+E	Power suppliable (kW)	8		
Mains switch	RCBO 16A 4P 6 kA 0,03A - AC type	Circuits protection	RCBO		
No. socket outlets	3	Socket-outlet 2P+E 16A - IEC 309	2		
Socket-outlet 3P+E 16A - IEC 309	1	Cable length	4 m		
Electrocod	139				

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS												
Saline solution	Acids		Bases		Solvents			Mineral	UV			
	Concentrated	Diluited	Concentrated	Diluited	Hexane	Benzol	Acetone	Alcohol	oil	rays		
Resistant	L <mark>imite</mark> d resistance	Resistant	Resistant	Resistant	L <mark>imited</mark> resistance	Not resistant	Not resistant	L <mark>imite</mark> d resistance	L <mark>imited</mark> resistance	L <mark>imite</mark> d res <mark>istan</mark> ce		

### **DIMENSIONAL**



# **TECHNICAL SYMBOLOGY**















STANDARDS/APPROVALS

