





## Sensors and potentiometers supply input 24Vdc / output 10Vdc 0.6A

<b>Series</b>	
Code	X766184
Type	CWCV7-6184 -
HS code	85049090
<b>INPUT TECHNICAL DATA</b>	
Input rated voltage	24 Vdc (16.8...30 Vdc)
Current consumption	30 mA at 10 Vdc
Internal protection fuse	T 1 A (external)
<b>OUTPUT TECHNICAL DATA</b>	
Output rated voltage	10 Vdc (9...11 Vdc adjustable)
Continuous current	60 mA
Overload limiting	yes
Ripple	
Status indication	LED "DC OK"
<b>GENERAL TECHNICAL DATA</b>	
Operating temperature range	-25...+60°C
Insulation	50 Vac / 60 s
Insulation type	2-way
Standard approvals	EN 50081-1, EN 50082-2, EN 61000-3-2
EMC Standard	EN61000-4-2, EN61000-4-4
Overvoltage category / pollution degree	II / 2
Protection degree	IP 20
Connection terminal IN / OUT	1.5 mm <sup>2</sup> / 1.5 mm <sup>2</sup> (screw)
Housing material	UL94V-0 plastic material
Dimensions (LxHxD)	6.2x92.5x90 mm
Approximate weight	35 g
Mounting information	on a rail, side by side
<b>ACCESSORIES</b>	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Plugin jumper red	CWBK 7-0802 (code X766802)
Plugin jumper white	CWBK 7-0804 (code X766804)
Plugin jumper blue	CWBK 7-0804 (code X766804)
APPROVALS AND MARKINGS	CE



\* Regulated switching converter\* Suitable for feeding potentiometers and sensors

## DESCRIZIONE DEL PRODOTTO

CWCV7-6184 Sensors and potentiometers supply input 24Vdc / output 10Vdc 0.6A