


Panther CCT Wallpack



- Durable compact wall mounted luminaire for general accent illumination and suitable for industrial applications
- All polycarbonate construction ideal for coastal and adverse weather applications
- Multiple conduit entry and BESA box fixing points
- Selectable CCT between 3000K, 4000K and 6500K output
- Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance
- Photocell and sensor options



OCTO
Option Available

Powered by **CASAMBI**

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
220-240V	50Hz	-10°C to 40°C	L80 60,000	Ra 80	6	110°	1	IP65	IK08

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	TRADE
APANLED	CCT Selectable	25W	3000/4000/6500K	2280lm (4000K)	91lm (4000K)	£79.50

CODE (OPTIONS)	DESCRIPTION	TRADE	CODE (OPTIONS)	DESCRIPTION	TRADE
/M3	Emergency	+ £90.00	/OCTO	OCTO Smart Control	+ £195.00
/SM3	Self-Test Emergency	+ £121.00	/PC	Electronic Photocell	+ £36.00
/DM3	DALI emergency	+ £205.00	/MWS	Integral Microwave Sensor	+ £60.00