










## DAMPPROOF E IP65




	EAN	l x w x h [mm]	W	V <sub>AC</sub>	Hz	lm	lm/W	K
DP 600 E 21W 840 VW IP65 GY	4099854080326	594x70x60	21	220-240	50/60	2835	135	4000
DP 600 E 21W 865 VW IP65 GY	4099854080340	594x70x60	21	220-240	50/60	2835	135	6500
DP 1200 E 42W 840 VW IP65 GY	4099854080364	1194x70x60	42	220-240	50/60	5670	135	4000
DP 1200 E 42W 865 VW IP65 GY	4099854080388	1194x70x60	42	220-240	50/60	5670	135	6500
DP 1500 E 52W 840 VW IP65 GY	4099854080401	1494x70x60	52	220-240	50/60	7020	135	4000
DP 1500 E 52W 865 VW IP65 GY	4099854080425	1494x70x60	52	220-240	50/60	7020	135	6500
DP 1500 E 52W 840 N IP65 GY	4099854080487	1494x70x60	52	220-240	50/60	6760	130	4000
DP 1500 E 52W 865 N IP65 GY	4099854080500	1494x70x60	52	220-240	50/60	6760	130	6500
DP 1500 E 52W 840 VN IP65 GY	4099854080449	1494x70x60	52	220-240	50/60	6760	130	4000
DP 1500 E 52W 865 VN IP65 GY	4099854080463	1494x70x60	52	220-240	50/60	6760	130	6500
DP 1500 E 66W 840 VW IP65 GY	4099854080524	1494x70x60	66	220-240	50/60	8910	135	4000
DP 1500 E 66W 865 VW IP65 GY	4099854080548	1494x70x60	66	220-240	50/60	8910	135	6500
DP 1500 E 66W 840 N IP65 GY	4099854080609	1494x70x60	66	220-240	50/60	8580	130	4000
DP 1500 E 66W 865 N IP65 GY	4099854080630	1494x70x60	66	220-240	50/60	8580	130	6500
DP 1500 E 66W 840 VN IP65 GY	4099854080562	1494x70x60	66	220-240	50/60	8580	130	4000
DP 1500 E 66W 865 VN IP65 GY	4099854080586	1494x70x60	66	220-240	50/60	8580	130	6500
DP 1500 E 80W 840 VW IP65 GY	4099854080654	1494x70x60	80	220-240	50/60	10800	135	4000
DP 1500 E 80W 865 VW IP65 GY	4099854080692	1494x70x60	80	220-240	50/60	10800	135	6500
DP 1500 E 80W 840 N IP65 GY	4099854080777	1494x70x60	80	220-240	50/60	10400	130	4000
DP 1500 E 80W 865 N IP65 GY	4099854080791	1494x70x60	80	220-240	50/60	10400	130	6500
DP 1500 E 80W 840 VN IP65 GY	4099854080715	1494x70x60	80	220-240	50/60	10400	130	4000
DP 1500 E 80W 865 VN IP65 GY	4099854080739	1494x70x60	80	220-240	50/60	10400	130	6500

	EAN	IP	IK	∇	R <sub>a</sub>	⊡ (°C)	PF	⊠
DP 600 E 21W 840 VW IP65 GY	4099854080326	65	08	120	>80	-20...+40	>0.88	0,57 kg
DP 600 E 21W 865 VW IP65 GY	4099854080340	65	08	120	>80	-20...+40	>0.88	0,57 kg
DP 1200 E 42W 840 VW IP65 GY	4099854080364	65	08	120	>80	-20...+40	>0.9	0,84 kg
DP 1200 E 42W 865 VW IP65 GY	4099854080388	65	08	120	>80	-20...+40	>0.9	0,84 kg
DP 1500 E 52W 840 VW IP65 GY	4099854080401	65	08	120	>80	-20...+40	>0.9	1,29 kg
DP 1500 E 52W 865 VW IP65 GY	4099854080425	65	08	120	>80	-20...+40	>0.9	1,29 kg
DP 1500 E 52W 840 N IP65 GY	4099854080487	65	08	90° x 60°	>80	-20...+40	>0.9	1,65 kg
DP 1500 E 52W 865 N IP65 GY	4099854080500	65	08	90° x 60°	>80	-20...+40	>0.9	1,65 kg
DP 1500 E 52W 840 VN IP65 GY	4099854080449	65	08	80° x 30°	>80	-20...+40	>0.9	1,59 kg
DP 1500 E 52W 865 VN IP65 GY	4099854080463	65	08	80° x 30°	>80	-20...+40	>0.9	1,59 kg
DP 1500 E 66W 840 VW IP65 GY	4099854080524	65	08	120	>80	-20...+40	>0.9	1,40 kg
DP 1500 E 66W 865 VW IP65 GY	4099854080548	65	08	120	>80	-20...+40	>0.9	1,40 kg
DP 1500 E 66W 840 N IP65 GY	4099854080609	65	08	90° x 60°	>80	-20...+40	>0.9	1,66 kg
DP 1500 E 66W 865 N IP65 GY	4099854080630	65	08	90° x 60°	>80	-20...+40	>0.9	1,66 kg
DP 1500 E 66W 840 VN IP65 GY	4099854080562	65	08	80° x 30°	>80	-20...+40	>0.9	1,76 kg
DP 1500 E 66W 865 VN IP65 GY	4099854080586	65	08	80° x 30°	>80	-20...+40	>0.9	1,76 kg
DP 1500 E 80W 840 VW IP65 GY	4099854080654	65	08	120	>80	-20...+40	>0.9	1,40 kg
DP 1500 E 80W 865 VW IP65 GY	4099854080692	65	08	120	>80	-20...+40	>0.9	1,40 kg
DP 1500 E 80W 840 N IP65 GY	4099854080777	65	08	90° x 60°	>80	-20...+40	>0.9	1,66 kg
DP 1500 E 80W 865 N IP65 GY	4099854080791	65	08	90° x 60°	>80	-20...+40	>0.9	1,66 kg
DP 1500 E 80W 840 VN IP65 GY	4099854080715	65	08	80° x 30°	>80	-20...+40	>0.9	1,78 kg
DP 1500 E 80W 865 VN IP65 GY	4099854080739	65	08	80° x 30°	>80	-20...+40	>0.9	1,78 kg







	[W]	Vac Hz	Max [W]	Max [A]	nx	Inrush current [A]	Th50 [μs]	B10	B16	B32	C10	C16	C32
DAMPPROOF 600 21W	21	220-240 50/60	420	6,89	20	7,60	12,3	65	98	209	65	104	209
DAMPPROOF 1200 42W	42	220-240 50/60	630	7,52	15	3,08	16,4	33	54	108	33	54	108
DAMPPROOF 1500 52W	52	220-240 50/60	624	7,44	12	4,04	9,1	27	43	87	27	42	87
DAMPPROOF 1500 66W	66	220-240 50/60	660	7,44	10	3,08	16,4	21	34	69	21	34	69
DAMPPROOF 1500 80W	80	220-240 50/60	720	7,60	9	3,08	16,4	20	33	66	20	33	66



C10449057  
G11168300

18.04.23

© LEDVANCE Ltd, Aquila House  
Delta Crescent, Westbrook, Warrington  
WA5 7NR, United Kingdom



LEDVANCE GmbH  
Steinerne Furt 62  
86167 Augsburg, Germany

[www.ledvance.com](http://www.ledvance.com)