

# PRODUCT DATASHEET HQL 80 W E27

HQL® | Mercury vapor lamps for open and enclosed luminaires



## Areas of application

- Factories and workshops
- Industrial installations
- Streets
- Car parks, courtyards
- Pedestrian zones, public squares
- Parks and gardens
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires




# **TECHNICAL DATA**

# Electrical data

Nominal wattage	80 W	
Construction wattage	80.00 W	
Nominal voltage	115 V 0.198 kVp	
Ignition voltage		
Operating mode	Conventional control gear (CCG) without ignitor	
Nominal current	0.8 A	
PFC capacitor at 50 Hz	8 µF	

## Photometrical data

Luminous flux	3800 lm
Luminous efficacy	48 lm/W
Color temperature	4100 K
Color rendering index Ra	50
Light color	541
Rated LLMF at 2,000 h	0.88
Rated LLMF at 4,000 h	0.83
Rated LLMF at 6,000 h	0.78
Rated LLMF at 8,000 h	0.75
Rated LLMF at 12,000 h	0.70
Rated LLMF at 16,000 h	0.65
Rated lamp efficacy (standard co.)	48 lm/W
UV protection	No



# **Dimensions & Weight**

Overall length	155.00 mm
----------------	-----------

Diameter	71 mm		
Product weight	56.00 g		
emperatures & operating conditions			
Maximum permitted outer bulb temperature	310 °C		
Maximum permitted base edge temperature	210 °C		
ifespan			
Rated lamp survival factor at 2,000 h	0.99		
Rated lamp survival factor at 4,000 h	0.97		
Rated lamp survival factor at 6,000 h	0.95		
Rated lamp survival factor at 8,000 h	0.90		
Rated lamp survival factor at 12,000 h	0.75		
Rated lamp survival factor at 16,000	0.68		
Rated lamp survival factor at 20,000 h	0.60		
Lifespan B10	8000 h		
Lifespan B5	6000 h		
Lifespan B50	24000 h		
Operation mode LLMF/LSF	50 Hz		
dditional product data			
Base (standard designation)	E27		
Mercury content	14.6 mg		
Mercury-free	No		
Design / version	Coated		
Product remark	As of April 2015 not compliant with ErP directive 245/2009		
apabilities			
Dimmable	No		
Burning position	Any		
Enclosed luminaire required	No		
ertificates & Standards			
Energy efficiency class	В		
Energy consumption	88.00 kWh/1000h		
ountry-specific categorizations			
ILCOS	QE/R-80-H/E/S-E27-71/155		
	27 142 14		

Order reference	HQL 80W E27

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	155.00 mm
Height	71 mm
Width	71 mm

## **DOWNLOAD DATA**

PDF

Documents and certificates
User instruction

Photometric and lighting design files
Spectral power distribution

## **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300012360	Round wrap 1	165 mm x 75 mm x 75 mm	71.00 g	0.93 dm³
4050300213200	Shipping box 40	424 mm x 355 mm x 356 mm	3742.57 g	53.59 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.