


PRODUCT-DETAILS

# S804U-K30

## S804U-K30 High Performance MCB



### General Information

Extended Product Type	S804U-K30
Product ID	2CCS864017R0527
EAN	7612271214197
Catalog Description	S804U-K30 High Performance MCB
Long Description	S804U-K30 4 Pole K Characteristic 30A 50kA 240/415VAC High Performance Circuit Breaker HPCB

### Technical

Standards	IEC/EN 60947-2 UL 489
Tripping Characteristic	K
Type of Residual Current	standard version
Rated Voltage ( $U_r$ )	acc. to IEC 60947-2 415 V AC
Rated Operational Voltage	acc. to IEC 60898-1 400 V
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 690 V
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV

Input Voltage Type	AC
Rated Current ( $I_n$ )	30 A
Rated Operational Current ( $I_e$ )	30 A
Rated Short-Circuit Capacity	(230 V) 40 kA (400 V) 40 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(230 V) 50 kA (400 V) 50 kA
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(230 V) 50 kA (400 V) 50 kA
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(415 V AC) 40 kA
Frequency (f)	50/60 Hz
Rated Frequency (f)	50/60 Hz
Power Loss	2.8 W at Rated Operating Conditions per Pole 0.7 W
Contact Position Indication	ON / OFF / TRIP
Energy Limiting Class	3
Number of Poles	4
Number of Protected Poles	4
Overvoltage Category	III
Release Type	K
Actuator Marking	I / O
Accessories Available	Yes
Connecting Capacity	Flexible 0 ... 50 mm <sup>2</sup> Rigid 0 ... 70 mm <sup>2</sup>

## Environmental

Ambient Temperature	-25...60 °C
Ambient Air Temperature	Operation -25 ... 60 °C
Degree of Protection	IP20
Pollution Degree	2
RoHS Status	Following EU Directive 2011/65/EU
RoHS Information	2CCC005116D0201 9AKK107680A3903
Environmental Information	2CCY413207D0203
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 50 kA
-----------------------------------	------------------

---

## Dimensions

---

Width in Number of Modular Spacings	6
Product Net Width	106 mm
Product Net Height	95 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	980 g
Size	4 modules
Built-In Depth (t <sub>2</sub> )	82.5 mm
Dimension Diagram	2CCC413003C0201

---



---

## Ordering

---

Minimum Order Quantity	1 piece
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	1010 g

---



---

## Certificates and Declarations

---

Declaration of Conformity - CE	2CCC005116D0201
--------------------------------	-----------------

---



---

## Installation

---

Instructions and Manuals	2CCC413015M0403
--------------------------	-----------------

---



---

## Popular Downloads

---

Data Sheet, Technical Information	2CCC413003C0208
-----------------------------------	-----------------

---



---

## Classifications

---

ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362020
UNSPSC	39121603
eClass	V11.0 : 27141901
IDEA Granular Category Code (IGCC)	4899 >> Miniature circuit breaker (MCB) screw-in model
Object Classification Code	F

---

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs → High Performance Circuit Breakers HPCBs

