## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

_	•			
Tyna	Ot.	liaht	source	٥.
IVDC	OI.	IIGIIL	Souic	ᠸ.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

## Product parameters

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
	nption in on- 00 h), rounded st integer	12	Energy efficiency class	D		
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	1 521 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	11,2	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90		
Outer dimen-	Height	108	Spectral power dis-	See image		
sions without	Width	60	tribution in the	in last page		
separate con- trol gear, light-	Depth	60	range 250 nm to 800 nm, at full-load			

ing control parts and non-lighting control parts, if any (millimetre)					
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	100		
		Chromaticity coordi-	0,458		
		nates (x and y)	0,410		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	50	Survival factor	0,90		
the lumen maintenance factor	0,93				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

