

IGA 24 IP54 (902 472)


- Easy visual inspection of the installed arresters through transparent door
- With integrated three-pole PE and twelve-pole N plug-in terminals
- With cable entry cover



Figure without obligation



Integrated plug-in terminal technology for PE and N conductors.



Dimension drawing IGA 24 IP54

Insulating enclosure for arresters with a capacity of 2x 12 modules; with integrated, elastic seal membrane for cable entry; ideally suited for feed-through wiring.

Type	IGA 24 IP54
Part No.	902 472
Degree of protection	IP 54
Type of cover	transparent door
Colour of enclosure	grey, RAL 7035
Number of cable entries	8x for cables Ø7-12 mm; 8x for cables Ø7-14 mm; 4x for cables Ø12-20 mm; 1x for cables Ø16.5-29 mm (top and bottom)
PE / N quantity x cross-section	6x 25 mm ² , 24x 4 mm ² , Cu
Capacity	24 modules (2x 12 modules), DIN 43880
Dimensions (W x H x D)	295 x 458 x 129 mm
Weight	2,39 kg
Customs tariff number	85389099
GTIN	4013364108950
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.