

# NOCTIS MAX

SLI029057NW\_PW



See  
more

Floodlight NOCTIS MAX, with a power of 200 W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK10 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Narrow beam angle 85° gives directional light so that selected surfaces can be better exposed. Designed for surface mounting.



Power	<b>200 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>17500 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>85 °</b>
IK	<b>10</b>	Degree of protection (IP)	<b>IP65</b>


## Technical data

Code	SLI029057NW_PW
Power	200 W
Nominal current	850 mA
Voltage	230 V
Energy consumption	200 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.99
Useful luminous flux*	17500 lm (120°)
Luminous flux**	17500 lm (360°)
Lamp efficacy	88 lm/W
Luminous intensity	10500 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	85 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	Aluminum+PC LENS
IK	10
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	410x290x30 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC




## Related documents



 User manual



 Declaration of Conformity



 Photometric file

