## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's n	name or tra	de mark:	<b>PHILIPS</b>
--------------	-------------	----------	----------------

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier: 9	9290035537
---------------------	------------

_	•			
Tyna	Ot.	liaht	source	٥.
IVDC	OI.	IIGIIL	Souic	ᠸ.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	G13 ROT		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

## **Product parameters**

Parameter		Value	Parameter	Value
		General product p	arameters:	
0,	nption in on- 00 h), rounded st integer	20	Energy efficiency class	E
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone errow cone (90º)	2 900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	20,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	1 513	Spectral power dis-	See image
sions without	Width	28	tribution in the	in last page
separate con- trol gear, light-	Depth	28	range 250 nm to 800 nm, at full-load	

ing control parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,434
		nates (x and y)	0,403
Parameters for LED and OLED light sources:			
R9 colour rendering index value 0 Survival factor 0,90		0,90	
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

