

# PRODUCT DATASHEET ENDURA Classic Cascade 50cm Post E27 Amber

ENDURA® CLASSIC CASCADE | Contemporary aluminium luminaires with amber or clear colored glass diffusor



### Areas of application

- Building facades
- Patios, balconies
- Pathway lighting
- Driveways

### **Product benefits**

- High flexibility in the choice of the light source thanks to E27 base
- Easy and quick installation

#### **Product features**

- Direct illumination
- Light cover material: glass
- Light cover appearance: amber or clear
- Housing material: aluminum
- Housing color: RAL 7016
- Type of protection: IP44



## **TECHNICAL DATA**

## **Electrical data**


| Nominal voltage  | 220240 V      |
|------------------|---------------|
| Mains frequency  | 5060 Hz       |
| Protection class | 1             |
| Operating mode   | Mains voltage |

### Photometrical data

| Photobiological safety group acc. to EN62778 | RG1 |
|--|-----|
| Photobiological safety group acc. to EN62471 | RGO |

## **Dimensions & Weight**

| Length         | 200.00 mm |
|----------------|-----------|
| Width          | 160.00 mm |
| Height         | 500.00 mm |
| Product weight | 1540.00 g |



## Materials & Colors

| Product color   | Dark gray |
|-----------------|-----------|
| Housing color   | Dark gray |
| Body material   | Aluminum  |
| Cover material  | Glass     |
| Mercury content | 0.0 mg    |

## Application & Mounting

| Type of connection                     | Terminal, 3-Pole (L, N, PE) |  |
|--|-----------------------------|--|
| Type of protection                     | IP44                        |  |
| Protection class IK (shock resistance) | IK03                        |  |
| Dimmable                               | No                          |  |
| Mounting type                          | Surface                     |  |
| Mounting location                      | Ground                      |  |
| Application environment                | Outdoor                     |  |
| With light source                      | No                          |  |
| Holder designation                     | E27                         |  |

## **Emergency lighting**

| Type of emergency light operation          | Non-maintained |  |
|--|----------------|--|
| Luminous flux in maintained operation mode | -              |  |
| Luminous flux in emergency operation mode  | -              |  |

## **Certificates & Standards**

| Chandrada |                 |
|-----------|-----------------|
| Standards | CE / EAC / UKCA |

## Additional product data

| Product remark        | Maximum bulb wattage: 25 W |
|-----------------------|----------------------------|
| Number of illuminants | 1                          |

## **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

## DOWNLOAD DATA

|     | Documents and certificates      |
|-----|---------------------------------|
| POF | User instruction                |
| PDF | Declarations Of Conformity CE   |
| PDF | Declarations Of Conformity UKCA |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075554290 | Folding box<br>1             | 180 mm x 220 mm x 520 mm             | 1752.00 g    | 20.59 dm <sup>3</sup> |
| 4058075554306 | Shipping box<br>2            | 540 mm x 380 mm x 240 mm             | 4609.00 g    | 49.25 dm³             |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.