

# PRODUCT DATASHEET HALOPIN OVEN 40 W 230 V G9

HALOPIN® OVEN | Halogen oven lamps



# Areas of application

- Baking ovens

# **Product benefits**

- Optimum halogen content for high temperatures
- Contains no mercury

# **Product features**

- Average life: 2,000 h




# **TECHNICAL DATA**

# **Electrical data**

Nominal wattage	40 W
Construction wattage	40.00 W
Nominal voltage	230 V

# Photometrical data

Luminous flux	230 lm
Luminous efficacy	5 lm/W
Color temperature	2700 К
Color rendering index Ra	100
Light color	1027



# Light technical data

Starting time	0 s
Dimensions & Weight	
Overall length	43.00 mm
Diameter	12.00 mm
Product weight	2.6 g

# Additional product data

Base (standard designation)	G9
Mercury-free	Yes

# Certificates & Standards

Energy efficiency class	G
Energy consumption	40.00 kWh/1000h

# **Country-specific categorizations**

Order reference	66740 OVEN AM 4

# Energy labelling regulation data acc EU 2019/2015

Non-directional or directionalNDLSMains or non-mainsMLSLight source cap-type (or other electric interface)G9Connected light source (CLS)NoColor-tuneable light sourceNoEnvelopeNoHigh luminance light sourceNoAnti-glare shieldNoCorrelated colour temperature typeSINGLE_VALUEClaim of equivalent powerNoHeight12.00 mmWidth12.00 mmChromaticity coordinate x0.460Chromaticity coordinate ySPHERE_360Beam angle correspondenceSPHERE_360Enrel D31186		
Mains or non-mainsMLSLight source cap-type (or other electric interface)G9Connected light source (CLS)NoColor-tuneable light sourceNoEnvelopeNoHigh luminance light sourceNoAnti-glare shieldNoCorrelated colour temperature typeSINGLE_VALUEClaim of equivalent powerNoHeight12.00 mmWidth12.00 mmChromaticity coordinate x0.4460Chromaticity coordinate ySPHERE_360Beam angle correspondenceSPHERE_360Enrel LD31186	Lighting technology used	OTHER
Light source cap-type (or other electric interface)G9Connected light source (CLS)NoColor-tuneable light sourceNoEnvelopeNoHigh luminance light sourceNoAnti-glare shieldNoCorrelated colour temperature typeSINGLE_VALUEClaim of equivalent power4.300 mmHeight12.00 mmKitchNeChromaticity coordinate x0.460Chromaticity coordinate ySPHERE_360EnvelopeSPHERE_360	Non-directional or directional	NDLS
Connected light source (CLS)NoColor-tuneable light sourceNoEnvelopeNoHigh luminance light sourceNoAnti-glare shieldNoCorrelated colour temperature typeSINGLE_VALUEClaim of equivalent powerNoLength12.00 mmHight12.00 mmChromaticity coordinate x0.460Chromaticity coordinate ySIHERE_360Enzel IDSINBLE_SAIL	Mains or non-mains	MLS
Color-tuneable light sourceNoEnvelopeNoHigh luminance light sourceNoAnti-glare shieldNoCorrelated colour temperature typeSINGLE_VALUEClaim of equivalent powerNoLength43.00 mmHeight12.00 mmWidth12.00 mmChromaticity coordinate x0.460Chromaticity coordinate ySINGLE_SINGLE_SINGLE_SINGLEEngthSPHERE_360Beam angle correspondenceSPHERE_360	Light source cap-type (or other electric interface)	G9
EnvelopeNoHigh luminance light sourceNoAnti-glare shieldNoCorrelated colour temperature typeSINGLE_VALUEClaim of equivalent powerNoLength43.00 mmHeight12.00 mmWidth12.00 mmChromaticity coordinate x0.460Chromaticity coordinate ySPHERE_360Beam angle correspondenceSPHERE_360	Connected light source (CLS)	No
High luminance light sourceNoAnti-glare shieldNoCorrelated colour temperature typeSINGLE_VALUEClaim of equivalent powerNoLength43.00 mmHeight12.00 mmWidth12.00 mmChromaticity coordinate x0.460Chromaticity coordinate y0.411Beam angle correspondenceSPHERE_360EPREL ID931186	Color-tuneable light source	No
Anti-glare shieldNoCorrelated colour temperature typeSINGLE_VALUEClaim of equivalent powerNoLength43.00 mmHeight12.00 mmWidth12.00 mmChromaticity coordinate x0.460Chromaticity coordinate y0.411Beam angle correspondenceSPHERE_360EPREL ID931186	Envelope	No
Correlated colour temperature type       SINGLE_VALUE         Claim of equivalent power       No         Length       43.00 mm         Height       12.00 mm         Width       12.00 mm         Chromaticity coordinate x       0.460         Chromaticity coordinate y       0.411         Beam angle correspondence       SPHERE_360         EPREL ID       931186	High luminance light source	No
Claim of equivalent power       No         Length       43.00 mm         Height       12.00 mm         Width       12.00 mm         Chromaticity coordinate x       0.460         Chromaticity coordinate y       0.411         Beam angle correspondence       SPHERE_360         EPREL ID       931186	Anti-glare shield	No
Length43.00 mmHeight12.00 mmWidth12.00 mmChromaticity coordinate x0.460Chromaticity coordinate y0.411Beam angle correspondenceSPHERE_360EPREL ID931186	Correlated colour temperature type	SINGLE_VALUE
Height       12.00 mm         Width       12.00 mm         Chromaticity coordinate x       0.460         Chromaticity coordinate y       0.411         Beam angle correspondence       SPHERE_360         EPREL ID       931186	Claim of equivalent power	No
Width       12.00 mm         Chromaticity coordinate x       0.460         Chromaticity coordinate y       0.411         Beam angle correspondence       SPHERE_360         EPREL ID       931186	Length	43.00 mm
Chromaticity coordinate x     0.460       Chromaticity coordinate y     0.411       Beam angle correspondence     SPHERE_360       EPREL ID     931186	Height	12.00 mm
Chromaticity coordinate y     0.411       Beam angle correspondence     SPHERE_360       EPREL ID     931186	Width	12.00 mm
Beam angle correspondence     SPHERE_360       EPREL ID     931186	Chromaticity coordinate x	0.460
EPREL ID 931186	Chromaticity coordinate y	0.411
	Beam angle correspondence	SPHERE_360
	EPREL ID	931186
Model number AC35349	Model number	AC35349

# DOWNLOAD DATA

Photometric and lighting design files
Spectral power distribution

# LOGISTICAL DATA

ጠ

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075390126	Folding box 1	25 mm x 23 mm x 70 mm	4.60 g	0.04 dm <sup>3</sup>
4058075390133	Shipping box 20	144 mm x 55 mm x 118 mm	114.00 g	0.93 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.