INESA

PRODUCT INFORMATION

Product code Product code (long) Product description EAN code Category

PHOTOMETRIC DATA

Nominal luminous flux	
Rated luminous flux	
Nominal beam angle (half-peak value)	
Rated beam angle (half-peak value)	
Correlated colour temperature	
Colour temperature designation	
Colour rendering index (Ra)	
Colour consistency	
Warm-up time to reach 60% of full light	

Number of switching cycles Warranty IE60090 IE-DL-DL150x-9-580-3000K-11 DL150 Downlight Square 9W 5999097600901 Downlight

580 lm 580 lm 110° 3000 K warm white 80 Ra 6 SDCM 1 s 15000

3 years

ELECTRICAL DATA

Nominal wattage	9 W
Rated wattage	9.0 W
Nominal voltage	100-240 V
Operating frequency	50-60 Hz
Power factor	0.9

MECHANICAL DATA

Overall length	147 mm
Overall width	147 mm
Overall height	21 mm
Weight	0,270 kg
Mounting	135 mm x 135 mm cuto

ADDITIONAL TECHNICAL INFORMATION

Starting time	0,5 s
Optimum operating ambient temperature	-20 °C to +40 °C
Dimming	non-dimmable
Electrical protection class	Class II

