



Modular screw terminal block 4mm², 3-poles, beige color



Model	Rated current (A)	Rated voltage (V)	Rated power (W)
T	32	500	16000
T	32	300	9600
T	32	250	8000
T	32	200	6400
T	32	150	4800
T	32	100	3200
T	32	75	2400
T	32	50	1600
T	32	25	800
T	32	15	480
T	32	10	320
T	32	5	160

Il presente catalogo è un documento di riferimento per il cliente. I dati tecnici sono quelli in vigore al momento della stampa. Cabur si riserva il diritto di modificare senza preavviso i prezzi e le condizioni di vendita. Per maggiori informazioni, consultare il sito internet www.cabur.it o il numero verde 800 20 20 20.

Series	BPL-TPL
Code	TP100
Type	TPL.4
HS code	85369010
Colour	Beige
TECHNICAL FEATURES	
Function/Type	Feed-through 3 poles
Rated cross-section	4 mm ²
Rated cross-section	
Connecting capacity	
Flexible wire	0.5-4 mm ²
Rigid wire	0.5-6 mm ²
Wire with ferrule - ferrule type	4 mm ² - WP40/16
Electrical characteristics according to IEC EN standard	
Maximum voltage AC/DC	500 V
Maximum current (rated cross-section)	32 A
Caliber	A4
Electrical characteristics according to UL Standard	
Maximum voltage AC/DC	300 V
Maximum current (rated cross-section)	20 A
Section (min-max)	18-12 (AWG)
Tightening torque value (UL)	4.4 lb.in
Electrical characteristics according to ATEX directive and IEC Ex standard	
Maximum voltage AC/DC	320 V
Maximum current (rated cross-section)	32 A
Operating temperature Min/Max	-40 °C / +110 °C
Rated impulse withstand voltage / pollution degree	6 kV / 3
Insulation stripping length	9 mm
Tightening torque value (nom. / max.)	0.5 / 0.7 Nm
Dimension	30x24x26 mm (AxBxH)
Insulation material temperature index (EN 60216-1)	130 °C
Plastic material	Polyamide UL94V-0
ACCESSORIES	
End section	-
Insulated bushing	-
APPROVALS AND MARKINGS	



* Panel mountable with M3 screw (max. 5.6 mm head diameter)* With dovetail joint for multiple connection
1 (1) When using BPL.4 and TPL.4 terminal blocks in Ex e classified installations, is required the insulated fixing screw

DESCRIZIONE DEL PRODOTTO

TPL.4 Modular screw terminal block 4mm², 3-poles, beige color