




## Screw

terminal block 2x25mm<sup>2</sup> for junction boxes

<b>Series</b>	CONT
<b>Code</b>	CONT225
<b>Type</b>	CONT/2/25
<b>Colour</b>	Transparent
<b>HS code</b>	85369010
<b>TECHNICAL FEATURES</b>	
<b>Function/Type</b>	Branch terminal
<b>Rated cross-section</b>	25 mm <sup>2</sup>
<b>Rated cross-section</b>	
<b>Connecting capacity</b>	
<b>N poles</b>	2
<b>Flexible wire</b>	-
<b>Rigid wire</b>	-
<b>Electrical characteristics according to IEC EN standard</b>	
<b>Maximum voltage AC/DC</b>	500 V
<b>Maximum current (rated cross-section)</b>	101 A
<b>Caliber</b>	-
<b>Electrical characteristics according to ATEX directive and IEC Ex standard</b>	
<b>Protection degree</b>	IP20
<b>Insulation stripping length</b>	10-20 mm
<b>Dimension</b>	24.5x10x25x26 mm (AxBxCxD)
<b>Insulation material temperature index (EN 60216-1)</b>	130 °C
<b>Plastic material</b>	Polycarbonate UL94V-0
<b>ACCESSORIES</b>	
<b>APPROVALS AND MARKINGS</b>	



\* 2, 3 and 5 poles for quick cabling\* Transparent and self-extinguishing body\* High dielectric strength\* High resistance to chemical and atmospheric agents  
1 IP20 protection degree

## DESCRIZIONE DEL PRODOTTO

CONT/2/25 Screw terminal block 2x25mm<sup>2</sup> for junction boxes