

PRODUCT DATASHEET DL SLIM FRAME SQ 155 WT

DOWNLIGHT SLIM SQUARE FRAME | Surface mounting frame, square shape



Areas of application

- General illumination
- Public areas
- Stairways
- Corridors
- Foyers
- Shops

Product benefits

- Cable entry on the side for electrical connection with low profil
- Easy installation thanks to included drilling template

Product features


- Low mounting depth
- Robust polycarbonate casing
- Mounting accessories included



TECHNICAL DATA

Dimensions & Weight

Length	170.0 mm
Width	170.0 mm
Height	38 mm
Product weight	68.00 g



Materials & Colors

Product color	White
Application & Mounting	
Mounting location	Ceiling / Wall
Certificates & Standards	
Ball shot safe	No

Safety advice

- All electrical connections must be made by a qualified person.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instruction	s User Instruction DL Slim Frame Square	
	Tender texts	Document name	
	Tender documents	DOWNLIGHT SLIM SQUARE FRAME 155 WT-EN	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075079410	Folding box	43 mm x 180 mm x 180 mm	119.00 g	1.39 dm ³
4058075079427	Shipping box	280 mm x 190 mm x 200 mm	902.00 g	10.64 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.