## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

## Model identifier: 8727900871586

## Type of light source:

| Lighting technology used:     | MH   | Non-directional or directional: | NDLS |  |  |
|-------------------------------|------|---------------------------------|------|--|--|
| Light source cap-type         | G8.5 |                                 |      |  |  |
| (or other electric interface) |      |                                 |      |  |  |
| Mains or non-mains:           | NMLS | Connected light source (CLS):   | No   |  |  |
| Colour-tuneable light source: | No   | Envelope:                       | No   |  |  |
| High luminance light source:  | No   |                                 |      |  |  |
| Anti-glare shield:            | No   | Dimmable:                       | No   |  |  |
| Product parameters            |      |                                 |      |  |  |

| Parameter                          |  | Value                     | Parameter   | Value        |  |  |
|------------------------------------|--|---------------------------|---|--------------|--|--|
| General product parameters:        |  |                           |   |              |  |  |
| 0,                                 | mption in on-<br>100 h), rounded<br>st integer                             | 21                        | Energy efficiency<br>class  | G            |  |  |
| indicating if it rain a sphere (30 | us flux (фuse),<br>efers to the flux<br>60º), in a wide<br>n a narrow cone | 1 750 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 3 000        |  |  |
| On-mode p<br>expressed in W        | oower (P <sub>on</sub> ),  | 20,1                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00         |  |  |
| for CLS, expres                    | dby power (P <sub>net</sub> )<br>ssed in W and<br>second decimal           | -                         | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 85           |  |  |
| Outer<br>dimensions<br>without     | Height   | 85                        | Spectral power  | See image    |  |  |
|                                    | Width  | 15                        | distribution in the   | in last page |  |  |
|                                    | Depth  | 15                        |   |              |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) |   | range 250 nm to 800<br>nm, at full-load |                |
|--|---|---|----------------|
| Claim of equivalent power <sup>(a)</sup>   | - | lf yes, equivalent power (W)            | -              |
|  |   | Chromaticity coordinates (x and y)      | 0,434<br>0,398 |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

