## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name of	r trade mark:	PHILIPS
--------------------	---------------	---------

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier: 9	9290022105
---------------------	------------

<b>-</b>	- 6	10 - 1- 1	
IVno	$\alpha$ T	IIσnt	CULILCO.
IVDC	vı	IIGIIL	source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	G13 ROT		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

## **Product parameters**

Froduct parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
_ · · · · ·	mption in on- 00 h), rounded st integer	16	Energy efficiency class	D
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in , in a wide cone arrow cone (90º)	2 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	16,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	tandby power expressed in W the second dec-	0,40	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	1 214	Spectral power dis-	See image
sions without	Width	28	tribution in the	in last page
separate con- trol gear, light-	Depth	28	range 250 nm to 800 nm, at full-load	

ing control parts and non-lighting control parts, if any (millimetre)					
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-	
			Chromaticity coordinates (x and y)	0,312 0,328	
Parameters for	Parameters for LED and OLED light sources:				
R9 colour rende	ring index value	0	Survival factor	0,90	
the lumen maintenance factor		0,96			
Parameters for	Parameters for LED and OLED mains light sources:				
displacement fa	ctor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6	
Claims that an I replaces a flu source without last of a particul	orescent light integrated bal-	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (P	st LM)	1,0	Stroboscopic effect metric (SVM)	0,9	

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

