



MASTERColour CDM-TC

MASTERC CDM-TC 35W/830 G8.5 1CT/12

Range of single-ended, very compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light

Warnings and Safety

- · Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- · Control gear must include end-of-life protection (IEC61167, IEC 62035)
- · Use only with electronic control gear. 35W/830 lamps may also use electromagnetic gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

Operating and Electrical					
Power Consumption	39.1 W				
Voltage (Nom)	88 V				
Voltage (Nom)	88 V				
General Information					
Cap-Base	G8.5 [G8.5]				
Operating Position	UNIVERSAL [Any or Universal (U)]				
Flux measurement reference	Sphere				
Light Technical					
Color Code	830 [CCT of 3000K]				
Luminous Flux	3,100 lumen				
Color Designation	Warm White (WW)				

Chromaticity Coordinate X (Nom)	0.434				
Chromaticity Coordinate Y (Nom)	0.398				
Correlated Color Temperature (Nom)	3000 K				
Luminous Efficacy (rated) (Nom)	79 lm/W				
Color rendering index (CRI)	81				
Controls and Dimming					
Dimmable	No				
Mechanical and Housing					
Bulb Finish	Clear				
Bulb Material	UV-Block Quartz				
Bulb Shape	T14 [T 14 mm]				


Datasheet, 2023, May 16 data subject to change

MASTERColour CDM-TC

Approval and Application	
Mercury (Hg) Content (Max)	3.1 mg
Mercury (Hg) Content (Nom)	3.1 mg
Energy Consumption kWh/1000 h	40 kWh
EPREL Registration Number	473,341
Product Data	
Full product code	871150020000615
Order product name	MASTERC CDM-TC 35W/830 G8.5 1CT/12


Order code	928085205125
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material number (12NC)	928085205125
Full product name	MASTERC CDM-TC 35W/830 G8.5 1CT/12
EAN/UPC - Case	8711500200013


Dimensional drawing



Product	D (max)	D	0	L (min)	L (max)	L	C (max)
MASTERC CDM-TC	15 mm	0.5 inch	5 mm	51 mm	53 mm	52 mm	85 mm
35W/830 G8.5 1CT/12							

Photometric data






Light Distribution Diagram - MASTERC CDM-TC 35W/830 G8.5 1CT/12

Spectral Power Distribution Colour - MASTERC CDM-TC 35W/830 G8.5 1CT/12

MASTERColour CDM-TC

Lifetime





Lumen Maintenance Diagram - MASTERC CDM-TC 35W/830 G8.5 1CT/12

Life Expectancy Diagram - MASTERC CDM-TC 35W/830 G8.5 1CT/12



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.