10390600

Valid from:

17.09.2018

DATA SHEET

EPIC® MCS 4 SS / MCS 4 BS UNIVERSALBUS



Description

- The mixed assembly guarantees high flexibility. For applications in mechanical and plant engineering, for printing machines and slide-in technology
- Assembly of individual connectors, suitable for different applications



Artikel No.	Module	VPE
10390600	Male	10
10390700	Female	10

General Characteristics

Series MC Module Number of Contacts 4 + shield

Termination Methods Screw termination: 0.08 - 1.5 mm²

Temperature Range -20°C to +85°C

Mechanical Characteristics

Cycles of mechanical operation 100

Electrical Characteristics

Rated Voltage 30 V
Rated Current 1 A
Pollution Degree 3

Creator: MANA2/PDP	Document: DB10390600EN	D 1 -f 0
Released: IVSE1/PDP	Version: 02	Page 1 of 2

10390600 Valid from: EPIC® MCS 4 SS / MCS 4 BS UNIVERSALBUS

DATA SHEET




Technical Drawing

17.09.2018











Automation



Industrial machinery and plant engineering



Wind Energy

Info

Power and signal modules can be used together in one housing

Application range

Plant engineering Light & sound technology Control engineering

Remark

Photographs are not to scale and do not represent detailed images of the respective products.