

# SLI037028NW\_PW

SLI037028NW\_PW

---

IK06



---

Power	<b>12 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1500 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>110 °</b>
IK	<b>06</b>	Degree of protection (IP)	<b>IP20</b>

---

## Technical data


---

Code	SLI037028NW_PW
Power	12 W
Nominal current	98 mA
Voltage	230 V
Energy consumption	12 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.5
Useful luminous flux*	1500 lm (360°)
Luminous flux**	1200 lm (360°)
Lamp efficacy	125 lm/W
Luminous intensity	420 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	110 °
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	170x35 mm
Mounting hole	145 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	Inside
Made in	PRC


## Related documents

---



 User manual



 Declaration of Conformity



 Photometric file



 3D model

---

