

VIGA

SLI045008WW_PW

Linear luminaire VIGA, with a power of 35 W, high light efficacy 120 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Suitable for both surface and suspended mounting.




| | | | |
|---------------------------|-----------------------|--------------------|---------------|
| Power | 35 W | Voltage | 230 V |
| Luminous flux* | 4200 lm (360°) | Colour temperature | 3000 K |
| Colour of light | WW | Beam angle | 120 ° |
| Degree of protection (IP) | IP20 | | |

Technical data


| | |
|------------------------------|---------------------------|
| Code | SLI045008WW_PW |
| Power | 35 W |
| Nominal current | 165 mA |
| Voltage | 230 V |
| Energy consumption | 35 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Power factor | 0.95 |
| Useful luminous flux* | 4200 lm (360°) |
| Luminous flux** | 3400 lm (360°) |
| Lamp efficacy | 120 lm/W |
| Colour temperature | 3000 K |
| Colour of light | WW |
| Beam angle | 120 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | PC |
| Degree of protection (IP) | IP20 |
| Colour | White |
| Dimension (AxBxC) | 76x1500x26 mm |
| For use | Inside |
| Assembly method | On the ceiling, Suspended |
| Application | Inside |
| Made in | PRC |

Related documents



 User manual



 Declaration of Conformity



 Photometric file