

# PRODUCT DATASHEET

## NIGHTLUX MOBILE LANTERN

NIGHTLUX LANTERN | Nightlights with motion sensor, multiple application areas, battery-powered



---

### Areas of application

- Kitchens, workspaces
- Children's bedrooms
- For indoor use only
- Nightlight

---

### Product benefits

- Attractive and functional design
- Multiple mounting options
- Accessories for flexible mounting options included

---

### Product features

- PIR motion detector and daylight sensor
- Color temperature: 4,000 K



## TECHNICAL DATA

### Electrical data

Nominal wattage	0.65 W
Nominal voltage	6 V
Nominal current	110.000 mA
Max. number of luminaires per miniature circuit breaker C10	-
Protection class	III
Operating mode	Battery

### Photometrical data

Luminous flux	30 lm
Luminous efficacy	30 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdc <sub>m</sub>
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0

### Dimensions & Weight

Length	73.00 mm
Width	51.00 mm
Height	160.00 mm
Product weight	82.00 g

### Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of protection	IP20
Dimmable	No
Mounting type	Standing
Mounting location	All surfaces
LED module replaceable	Not replaceable
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	25000 h <sup>1)</sup>
---------------------------	-----------------------

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Sensor

Type of sensor	Light / Motion
----------------	----------------

### BATTERY

Type of Battery	Alkaline
Battery size [GMS]	AAA
Number of included batteries	4
Nominal voltage of battery	1.5 V

### Certificates & Standards

Standards	CE / UKCA
-----------	-----------

### DOWNLOAD DATA

#### Documents and certificates



Declarations Of Conformity CE



Declarations Of Conformity UKCA

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075570184	Blister 1	52 mm x 140 mm x 210 mm	103.00 g	1.53 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075570191	Shipping box 6	358 mm x 153 mm x 231 mm	905.00 g	12.65 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.