


Swift Bulkhead



- IP65 Compact Emergency Bulkhead
- Supplied with self-adhesive legend
- Optic design provides optimum performance for escape route lighting
- Side and rear cable entries
- Screwless gear tray for ease of installation
- Viewing distance 17 metres



***	Escape route 2 metres wide (1 Lux minimum) *			
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5	1.48	5	1.48	5.6
4	1.2	4	0.72	4.5
6	-	-	-	-

***	Open (Anti-Panic) area (0.5 Lux Minimum) **			
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5	2.5	6	1.98	6
4	2.24	7.5	1.98	6
6	2.24	5.9	1.98	5.79

INPUT	HERTZ	TEMP	LIFETIME (HRS)	BEAM ANGLE	CLASS	IP	IK
230V	50Hz	0°C to 40°C	L70 50,000	105°x120°	1	IP65	IK08

CODE	DESCRIPTION	WATTAGE	CCT	STANDARD MODE	EMERGENCY MODE	TRADE
ASWTLED/3M	Daylight - Maintained / Non-Maintained	3W	6500K	173lm	64lm	£48.60

CODE (ACCESSORIES)	DESCRIPTION	TRADE
ASBP/1	3.6V 600mAh Ni-Cd Replacement Battery	£11.30

