Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier: 8711500716712

Type of light source:

| Lighting technology used: | other | Non-directional or directional: | NDLS | | |
|-------------------------------|-------|---------------------------------|------|--|--|
| Light source cap-type | G5 | | | | |
| (or other electric interface) | | | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No | | |
| Colour-tuneable light source: | No | Envelope: | - | | |
| High luminance light source: | No | | | | |
| Anti-glare shield: | No | Dimmable: | Yes | | |
| Product parameters | | | | | |

| Product parameters | | | | | | |
|--|-----------------------------------|-------------------------|---|--------------|--|--|
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| Energy consum mode (kWh/100 up to the neares | 00 h), rounded | 14 | Energy efficiency class | G | | |
| Useful luminou indicating if it re in a sphere (36 cone (120 ^o) or in (90 ^o) | efers to the flux 50°), in a wide | 740 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 500 | | |
| On-mode p expressed in W | ower (P _{on}), | 13,1 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | |
| Networked stand for CLS, expres rounded to the s | sed in W and | - | Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set | 72 | | |
| Outer | Height | 531 | Spectral power | See image | | |
| dimensions | Width | 16 | distribution in the | in last page | | |
| without | Depth | 16 | 1 | Page 1/3 | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | |
|--|---|---|----------------|
| Claim of equivalent power ^(a) | - | lf yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,313 0,337 |

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

