



CoreLine Highbay Gen5

BY121P G5 LED200S/865 PSU NB

- Power supply unit (ON/OFF) - Beam angle 55° - 55°

CoreLine Highbay Gen5 delivers on the CoreLine promise of innovative, easy-to-use and high-quality luminaires. A reliable, highly-efficient luminaire with a very long-lifetime, it delivers great energy savings and requires less maintenance. At the same time, CoreLine Highbay is very easy to handle. The luminaire can be installed on your existing grid and the electrical connection is a straightforward task, with no need to open the luminaire and an external IP65 connector. With a choice of two beam angles: narrow and wide beam, you can adjust your lighting plan to suit your exact needs. This range also includes Interact Ready luminaires with integrated wireless communications and integrated movement and daylight sensors. So CoreLine Highbay Gen5 is ready to be used with any Interact connected lighting system.

Product data

| General Information | | Protection class IEC | Safety class I |
|-------------------------------|-----------------------------------|--|--|
| Light source color | 865 cool daylight | Glow-wire test | Temperature 650 °C, duration 30 s |
| Light source replaceable | No | Flammability mark | For mounting on normally flammable surfaces |
| Number of gear units | 1 unit | CE mark | Yes |
| Driver/power unit/transformer | Power supply unit (ON/OFF) | ENEC mark | ENEC mark |
| Driver included | Yes | Warranty period | 5 years |
| Optic type | Beam angle 55° | Constant light output | No |
| Luminaire light beam spread | 55° | Number of products on MCB of 16 A type B | 6 |
| Control interface | - | Photobiological risk | Photobiological risk group 1 @200mm to EN62778 |
| Connection | Connection unit 3-pole | | |
| Cable | Cable 0.3 m with connector 3-pole | | |

CoreLine Highbay Gen5

| | |
|------------------------------------|---------|
| Photobiological risk specification | 18.2 m |
| EU RoHS compliant | Yes |
| Unified glare rating CEN | 22 |
| Lighting Technology | LED |
| Brand | Philips |

Light Technical

| | |
|---------------------------------|--------------|
| Luminous Flux | 20,000 lumen |
| Saturated Red (R9) | <50 |
| Luminous Efficacy (rated) (Nom) | 159 lm/W |
| Color rendering index (CRI) | >80 |
| Flickering value (PstLM) | 0.5 |
| Stroboscopic effect value (SVM) | 1 |

Operating and Electrical

| | |
|-------------------------|--------------|
| Input Voltage | 220 to 240 V |
| Line Frequency | 50 or 60 Hz |
| Input Frequency | 50 or 60 Hz |
| Power Consumption | 126 W |
| Inrush current | 40 A |
| Inrush time | 600 ms |
| Power Factor (Fraction) | 0.95 |

Temperature

| | |
|---------------------------|---------------|
| Ambient temperature range | -30 to +50 °C |
|---------------------------|---------------|

Controls and Dimming

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Mechanical and Housing

| | |
|-----------------------------|-------------------|
| Housing Material | Aluminum die-cast |
| Reflector material | - |
| Optic material | Polycarbonate |
| Optical cover/lens material | Polycarbonate |
| Fixation material | - |
| Housing Color | Dark gray |
| Optical cover/lens finish | Clear |
| Overall height | 99 mm |
| Overall diameter | 330 mm |

Approval and Application

| | |
|-------------------------|--|
| Ingress protection code | IP65 [Dust penetration-protected, jet-proof] |
|-------------------------|--|

| | |
|------------------------------|-----------------------------|
| Mech. impact protection code | IK08 [5 J vandal-protected] |
| Sustainability rating | - |

Initial Performance (IEC Compliant)

| | |
|-------------------------------|-----------------------|
| Luminous flux tolerance | +/-10% |
| Init. Corr. Color Temperature | 6500 K |
| Initial chromaticity | (0.316, 0.332) SDCM<5 |
| Power consumption tolerance | +/-10% |

Over Time Performance (IEC Compliant)


| | |
|--|------|
| Control gear failure rate at median useful life 50000 h | 5 % |
| Control gear failure rate at median useful life 100000 h | 10 % |
| Lumen maintenance at median useful life* 50000 h | L85 |
| Lumen maintenance at median useful life* 100000 h | L65 |

Application Conditions

| | |
|------------------------------------|----------------|
| Performance ambient temperature Tq | 35 °C |
| Maximum dim level | Not applicable |
| Suitable for random switching | Yes |

Product Data

| | |
|---------------------------------|------------------------------|
| Full product code | 871951495576900 |
| Order product name | BY121P G5 LED200S/865 PSU NB |
| EAN/UPC - Product | 8719514955769 |
| Order code | 911401630208 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 1 |
| Material number (12NC) | 911401630208 |
| Net weight | 2.690 kg |
| Full product name | BY121P G5 LED200S/865 PSU NB |
| EAN/UPC - Case | 8719514955769 |



CoreLine Highbay Gen5

Dimensional drawing

