

PRODUCT DATASHEET TruSys[®] PFM ENERGY RAIL 8P 3000

TruSys® PERFORMANCE ENERGY RAIL 8 POLE | 8-pole mounting rail

A State of the sta

Areas of application

- Industry halls, high rack warehouse, garages, hardware stores

Product benefits

- Simple installation
- High flexibility thanks to two available lengths (1500 mm, 3000 mm and 1500 mm end rail)

Product features

- Through wired with 8 core cable
- Different lenghts available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors



TECHNICAL DATA

Dimensions & Weight

Length	3150 mm
Width	70.2 mm
Height	38.8 mm
Product weight	3260.00 g

Materials & Colors

Product color	White
---------------	-------

Application & Mounting

Ambient temperature range	-25+60 °C
Type of protection	IP20
Mounting type	Surface
Mounting location	Ceiling
With light source	No

Certificates & Standards

Standards	CE

EQUIPMENT / ACCESSORIES

- Various accessories available

DOWNLOAD DATA

	Documents and certificates
POF	User instruction
	CAD/BIM files
	CAD_STEP_3D
	Tender texts
1	Tender documents

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075354784	Shipping box 1	3,170 mm x 88 mm x 56 mm	3797.00 g	15.62 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.