

ASPS 110 420 S L (767 573)

- Insulating stick with plug-in coupling as end fitting for extending the handle
- In a suitable storage bag



Parts list:			
Pos.	Part No.	Pos.	Part No.
1	767 576	6	767 564
2	767 577	7	766 369
3	767 591	8	767 574
4	767 592	9	767 996
5	767 593		
_			

For more detailed information on these products, see Accessories chapter.

Figure without obligation

Туре	ASPS 110 420 S L	
Part No.	767 573	
Nominal voltage (U _N)	110 420 kV	
Type of voltage	a.c.	
Frequency	50 Hz	
Total length (I _G)	1000 mm	
Category	S/L	
Temperature range	−25 °C +55 °C	
For use at	.	
For	Overhead lines and outdoor switching stations	
Application	Switchgear installations and overhead lines or overhead lines	
Design	Single-pole	
Indication	Acoustic and visual	
Self-testing element	Yes	
Material (indicator)	Plastic, fully insulated (black)	
Material (electric field sensor) Plastic (black)		
aterial (insulating stick) Glass-fibre reinforced polyester tube		
Veight 3,57 kg		
Customs tariff number	90303370	
GTIN	4013364134270	
PU	1 Stk	

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.