Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's | name o | or trade | mark: | PHILIPS |
|------------|--------|----------|-------|---------|
|------------|--------|----------|-------|---------|

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| Model identifier: | 8727900840551 |
|-------------------|---------------|
|-------------------|---------------|

| _ | • | | | |
|------|-----|-------|-----------------|---|
| Typa | Λt | liaht | source | • |
| IVDE | VI. | HEILL | 3 Uul CE | |

| Lighting technology used: | other FL | Non-directional or directional: | NDLS | |
|-------------------------------|----------|---------------------------------|------|--|
| Light source cap-type | G10Q | | | |
| (or other electric interface) | | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No | |
| Colour-tuneable light source: | No | Envelope: | - | |
| High luminance light source: | No | | | |
| Anti-glare shield: | No | Dimmable: | Yes | |
| Product parameters | | | | |

Product parameters

| Parameter | | Value | Parameter | Value | |
|---|--|---------------------------|--|--------------|--|
| | General product parameters: | | | | |
| | mption in on- 100 h), rounded st integer | 33 | Energy efficiency class | G | |
| indicating if it r in a sphere (3 | us flux (фuse), efers to the flux 60º), in a wide n a narrow cone | 2 310 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 500 | |
| On-mode pressed in W | oower (P _{on}), | 32,8 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 | |
| Outer | Height | 31 | Spectral power | See image | |
| dimensions | Width | 304 | distribution in the | in last page | |
| without | Depth | 304 | | Page 1 / 3 | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | |
|--|---|---|----------------|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,313 0,337 |

(a)'-': not applicable; (b)'-': not applicable;

