

PRODUKTDATENBLATT FX-DCS -G1-CM2PJ-IP67-SIDEKIT5

LINEARlight FLEX® DIFFUSE | – Accessories for side-bending



Anwendungsgebiete

- Architectural Integration – e.g. coves, walls
- Ceiling integration
- Recessed lighting
- Cove lighting
- Shelf and furniture lighting

Produktvorteile


- Kurze Montagezeit (CONNECTsystem)

Produkteigenschaften

- Can be easily combined with covers for homogeneous light distribution
- Clips for easy installation and maintenance
- Compatible with Linearlight Flex
- Ideal even for lighting in confined spaces
- Compatible with TEC Flex



TECHNISCHE DATEN

Maße & Gewicht



Länge	260,0 mm
Breite	150 mm
Höhe	30,0 mm
Produktgewicht	98,1 g

DOWNLOADS

DOWNLOADS	
	User instruction
	Advertisements

VERPACKUNGSMITTEL

EAN	Verpackungseinheit (Stück pro Einheit)	Abmessungen (Länge x Breite x Höhe)	Bruttogewicht	Volumen
4052899452077	BAG 1	260 mm x 150 mm x 30 mm	106.10 g	1.17 dm ³
4052899452084	Versandschachtel 10	195 mm x 295 mm x 160 mm	1226.00 g	9.20 dm ³

Die genannten Produktnummern beschreiben die kleinste bestellbare Mengeneinheit. Eine Versandeinheit kann mehrere Einzelprodukte beinhalten. Als Bestellmenge verwenden Sie bitte das Ein- oder Mehrfache einer Versandeinheit.

Haftungsausschluss

Änderungen und Irrtümer vorbehalten. Vergewissern Sie sich, dass Sie immer den neuesten Stand verwenden.