

PRODUCT-DETAILS

## **FPW38** INSUL PIERCING WASHER CU 3/8 STUD



General Information		
Extended Product Type	FPW38	
Product ID	7TAI029030R0032	
EAN	5414363113362	
Catalog Description	INSUL PIERCING WASHER CU 3/8 STUD	
Long Description	Insulation Piercing Washer, Outer Diameter 25.4mm (1.0 Inch), Inner Diameter 10.9mm (0.43 Inch), Stud Size 3/8 Inch, Copper Alloy, Tin Plated	

Ordering	
EAN	5414363113362
UPC	786210709963
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	250 piece
Package Level 1 Width	3 in
	76 mm
Package Level 1 Height	3 in
	76 mm
Package Level 1 Depth /	3.5 in
Length	89 mm

© 2023 ABB. All rights reserved.

Subject to change without notice

Package Level 2 Units	2500 piece
Package Level 2 Width	7.5 in
	191 mm
Package Level 2 Height	3.5 in
	89 mm
Package Level 2 Depth /	16.5 in
Length	419 mm

Application	Enables copper to aluminum connections to be made in a bolted joint without the use of inhibiting compounds.
Brand / Label	Sta-Kon
Effective Date	19890303
Inside Diameter	0.43 in 10.9 mm
Material	Copper
Outside Diameter	1.0 in 25.4 mm
Product Name	COPPER WASHER
Product Type	Transition Washer
Special Functions	Accommodates the difference in thermal expansion between copper and aluminum and enhances the efficiency of bolted grounding connections.
Standards	UL E9809
Sub Brand / Label	Dragon Tooth
Suitable For	3/8 Inch
Surface Finishing	Tin Plated
Thickness	0.035 in 0.89 mm

## **Certificates and Declarations**

Data Sheet, Technical Information

Classifications		
ETIM 6	EC002345 - Serrated lock washer	
ETIM 7	EC002345 - Serrated lock washer	
ETIM 8	EC002345 - Lock washer	
UNSPSC	31161807	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category	2885 >> Flat washers	
Code (IGCC)		

## Categories

Low Voltage Products and Systems  $\rightarrow$  Installation Products  $\rightarrow$  Wire Management and Connectivity  $\rightarrow$  Compression & Mechanical Connectors

FPW38

