## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or tr | ade mark: PHILIPS |
|-----------------------|-------------------|
|-----------------------|-------------------|

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| _    | •   |       |      |      |
|------|-----|-------|------|------|
| Type | Λt  | liaht | COLL | rco. |
| IVDE | UI. | HEIIL | 3UU  | ıce. |

| Lighting technology used:     | LED  | Non-directional or directional: | NDLS                            |
|-------------------------------|------|---------------------------------|---------------------------------|
| Light source cap-type         | G5   |                                 |                                 |
| (or other electric interface) |      |                                 |                                 |
| Mains or non-mains:           | NMLS | Connected light source (CLS):   | No                              |
| Colour-tuneable light source: | No   | Envelope:                       | -                               |
| High luminance light source:  | No   |                                 |                                 |
| Anti-glare shield:            | No   | Dimmable:                       | Only with spe-<br>cific dimmers |

## **Product parameters**

| Froduct parameters                                |   |                           |  |              |
|---|---|---------------------------|--|--------------|
| Parameter   |   | Value                     | Parameter  | Value        |
| General product parameters:                       |   |                           |  |              |
| Energy consur<br>mode (kWh/10<br>up to the neares | 00 h), rounded  | 26                        | Energy efficiency class  | D            |
| dicating if it refe<br>a sphere (360º)            | s flux (фuse), in-<br>ers to the flux in<br>, in a wide cone<br>rrow cone (90º) | 3 900 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000        |
| On-mode pow<br>pressed in W                       | ver (P <sub>on</sub> ), ex-   | 26,0                      | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |
| (P <sub>net</sub> ) for CLS, 6                    | andby power expressed in W the second dec-                                      | -                         | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 80           |
| Outer dimen-                                      | Height  | 1 163                     | Spectral power dis-  | See image    |
| sions without                                     | Width   | 19                        | tribution in the   | in last page |
| separate con-<br>trol gear, light-                | Depth   | 19                        | range 250 nm to 800<br>nm, at full-load  |              |

| ing control parts and non- lighting con- trol parts, if any (millime- tre) |      |                              |       |
|--|------|------------------------------|-------|
| Claim of equivalent power <sup>(a)</sup>                                   | -    | If yes, equivalent power (W) | -     |
|  |      | Chromaticity coordi-         | 0,382 |
|  |      | nates (x and y)              | 0,380 |
| Parameters for LED and OLED light sources:                                 |      |                              |       |
| R9 colour rendering index value  | 0    | Survival factor              | 0,90  |
| the lumen maintenance factor   | 0,96 |                              |       |

(a)'-': not applicable; (b)'-': not applicable;

