

| Description                    |      | Comments         |
|--------------------------------|------|------------------|
| Thorgeon Cod                   |      | 05004            |
| Thorgeon EAN                   |      | 4751029890658    |
| Model                          | .... | SN-T 250W E40    |
| Power                          | W    | 250              |
| Bulb Finish                    |      | Clear            |
| Bulb Shape                     |      | Tubular          |
| Cap Base                       | .... | E40 4 CUTS       |
| Lamp Current(Nom)              | A    | 3                |
| Lamp Voltage(Min)              | V    | 85               |
| Lamp Voltage(Nom)              | V    | 100              |
| Lamp Voltage(Max)              | V    | 115              |
| Ignition Supply Voltage(Max)   | V    | 198              |
| Ignition Peak Voltage(Max)     | V    | 2800             |
| Ignition TIME(Max)             | S    | 5                |
| Color Temperature              | K    | 2000(2200)       |
| Life to 5% Failures(Nom)       | H    | 12000            |
| Life to 20% Failure(Nom)       | H    | 20000            |
| Life to 50% Failure(Nom)       | H    | 28000            |
| System Description             |      | External Ignitor |
| Lm/w                           | lm/W | 120              |
| Luminous Efficiency            | lm   | 30000            |
| PPF maintenance 2000h          |      | 95%              |
| PPF maintenance 5000h          |      | 98%              |
| PPF maintenance 10000h         |      | 92%              |
| PPF maintenance 12000h         |      | 96%              |
| Color rendering                | IRC  | 21               |
| Run-up Time                    | Min  | 5                |
| Net Weight(Pieces)             | Kg   | 0,135            |
| Diameter(Max)                  | mm   | 47               |
| Length(Max)                    | mm   | 254              |
| Operating Position             |      | Universal        |
| Energy Consumption Kwh/1000h   | Kwh  | 275              |
| Max temperature Permitted Bulb | °C   | 450              |
| Max temperature Permitted Base | °C   | 250              |

## SN-T 250W E40 05004

