


IP65 Falcon Surface Emergency Downlight



- Compact surface ultra-low profile recessed self-test emergency downlight
- Supplied with open area and escape route interchangeable lenses
- High specification optic design and performance allows increased spacing providing reduced cost
- Available in black and white finishes
- Up to 19.6 metres spacing between luminaires
- Self-test as standard
- BESA mounting option



White








Black








Open Area Lens



Escape Route Lens

 AFALED/ER/3NM/ST AFALED/ER/3NM/ST/B	Escape route 2 metres wide (1 Lux minimum) *				
	***				
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial	
2.5	-	-	4.2	10.5	
4	-	-	4.25	13	
2.5	-	-	4	9.5	
4	-	-	4	11	

 AFALED/OA/3NM/ST AFALED/OA/3NM/ST/B	Open (Anti-Panic) area (0.5 Lux Minimum)**				
	***				
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial	
2.5	2.5	4.5	2.5	4.5	
4	3	7	3	7	
6	3.5	9	3.5	9	
2.5	2.3	4	2.3	4	
4	2.8	6.5	2.8	6.5	
6	3.5	9	3.5	9	

INPUT	HERTZ	TEMP	LIFETIME (HRS)	BEAM ANGLE	CLASS	IP	IK
230V	50Hz	0°C to 40°C	L70 50,000	Open area - 96° / Escape route - 135°x17°	1	IP65	IK08

CODE	DESCRIPTION	WATTAGE	CCT	EMERGENCY MODE	TRADE
AFALED/3NM/ST/IP65	Non-Maintained	3W	6500K	Open area - 153lm Escape route - 145lm	£62.50
AFALED/3NM/ST/IP65/B	Non-Maintained - Black				£62.50

CODE (ACCESSORIES)	DESCRIPTION	TRADE
ASBP/14/LI	3.2V 3000mAh Li-FePO4 Replacement Battery	£11.30