## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	PELLOATED REGOT	LATION (LO) 2019/2	ots with regard to energ	gy labelling of light		
Supplier's name	e or trade mark:	PHILIPS				
Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL						
Model identifie	er: 87182912027	45				
Type of light so	urce:					
Lighting techno	logy used:	МН	Non-directional or directional:	DLS		
Light source cap-type		GX10				
(or other electric interface)						
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable	e light source:	No	Envelope:	No		
High luminance	light source:	No				
Anti-glare shield	d:	No	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
		General product p				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		21	Energy efficiency class	G		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		880 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode pexpressed in W	oower (P <sub>on</sub> ),	20,1	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	84		
Outer	Height	65	Spectral power	See image		
dimensions	Width	51	distribution in the	in last page		
without	Depth	51		Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any		range 250 nm to 800 nm, at full-load				
(millimetre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity	0,434			
		coordinates (x and y)	0,398			
Parameters for directional light sources:						
Peak luminous intensity (cd)	14 500	Beam angle in degrees, or the range of beam angles that can be set	10			

(a)'-': not applicable; (b)'-': not applicable;

