

PRODUCT DATASHEET

HQI-T 250 W/D PRO

POWERSTAR HQI®-T | Metal halide lamps with quartz technology for enclosed luminaires



Areas of application

- Factories and workshops
- Sports halls and multi-purpose halls
- Industrial installations
- Docks and port facilities
- Marshaling yards, container transshipment facilities
- Buildings, monuments, bridges
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- E40 screw base for simple lamp handling
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

Product features

- POWERSTAR® quartz technology
- Light colors: neutral white (N), daylight (D)



TECHNICAL DATA


Electrical data

| | |
|------------------------|---|
| Nominal wattage | 250 W |
| Construction wattage | 260.00 W |
| Nominal voltage | 105 V |
| Ignition voltage | 4.0/5.0 kVp ¹⁾ |
| Operating mode | Conventional control gear (CCG) and ignitor |
| Nominal current | 3 A |
| PFC capacitor at 50 Hz | 32 µF |

1) Minimum / Maximum

Photometrical data

| | |
|--------------------------|----------|
| Luminous flux | 18000 lm |
| Luminous efficacy | 69 lm/W |
| Color temperature | 5500 K |
| Color rendering index Ra | ≤ 87 |
| Light color | 855 |
| Rated LLMF at 2,000 h | 0.95 |
| Rated LLMF at 4,000 h | 0.92 |
| Rated LLMF at 6,000 h | 0.90 |
| Rated LLMF at 8,000 h | 0.87 |
| Rated LLMF at 12,000 h | 0.85 |
| Rated LLMF at 16,000 h | 0.81 |
| UV protection | Yes |



Dimensions & Weight

| | |
|----------------|-----------|
| Overall length | 226.00 mm |
|----------------|-----------|

| | |
|---------------------------|----------|
| Light center length (LCL) | 150 mm |
| Diameter | 46 mm |
| Product weight | 150.00 g |

Temperatures & operating conditions

| | |
|--|--------|
| Maximum permitted outer bulb temperature | 500 °C |
| Maximum permitted base edge temperature | 250 °C |

Lifespan

| | |
|--|---------|
| Rated lamp survival factor at 2,000 h | 0.98 |
| Rated lamp survival factor at 4,000 h | 0.96 |
| Rated lamp survival factor at 6,000 h | 0.94 |
| Rated lamp survival factor at 8,000 h | 0.92 |
| Rated lamp survival factor at 12,000 h | 0.88 |
| Rated lamp survival factor at 16,000 | 0.81 |
| Lifespan B50 | 16000 h |

Additional product data

| | |
|-----------------------------|---------|
| Base (standard designation) | E40 |
| Mercury content | 21.0 mg |
| Design / version | Clear |

Capabilities

| | |
|-----------------------------|-----|
| Dimmable | No |
| Burning position | Any |
| Enclosed luminaire required | Yes |
| Hot restart | No |

Certificates & Standards

| | |
|-------------------------|------------------|
| Energy efficiency class | G |
| Energy consumption | 260.00 kWh/1000h |

Country-specific categorizations





| | |
|-----------------|---------------------------------|
| ILCOS | MT/UB-250/952-H/E/SL-E40-46/226 |
| Order reference | HQI-T 250W/D PR |

Energy labelling regulation data acc EU 2019/2015

| | |
|--------------------------|----|
| Lighting technology used | MH |
|--------------------------|----|

| | |
|---|--------------|
| Non-directional or directional | NDLS |
| Mains or non-mains | NMLS |
| Light source cap-type (or other electric interface) | E40 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | SECOND |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | No |
| Length | 226.00 mm |
| Height | 46 mm |
| Width | 46 mm |
| Chromaticity coordinate x | 0,333 |
| Chromaticity coordinate y | 0,340 |
| Beam angle correspondence | SPHERE_360 |
| EPREL ID | 546555 |
| Model number | AC34329 |

DOWNLOAD DATA

| Documents and certificates | |
|---|-------------------------------|
|  | User instruction |
|  | Declarations Of Conformity CE |
|  | Certificates |
| Photometric and lighting design files | |
|  | Spectral power distribution |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4008321677846 | Sleeve 1 | 51 mm x 51 mm x 260 mm | 175.80 g | 0.68 dm ³ |

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4008321677853 | Shipping box 12 | 216 mm x 166 mm x 272 mm | 2304.00 g | 9.75 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.