

PRODUCT-DETAILS

# E232E-230N

## E232E-230N Staircase Switch



### Informations générales

Extension du type de produit	E232E-230N
Code de produit	2CDE110003R0511
EAN	4016779654166
Description courte	E232E-230N Staircase Switch

**Description longue**

Staircase time switches with off-delay are operated by push-buttons, which are often equipped with a glow lamp. The switch levers are designed for a glow lamp current of up to 150 mA and are therefore excellently suited for installations in multistorey buildings. The E 232E-230 staircase lighting timer with off-delay has an electromechanical timer relay with synchronous motor drive, which ensures a high level of operational safety in any installation position. The time range can be set in 15-second increments from one to seven minutes. Can be reswitched after 30s. The multifunctional units of the E 232E-230 Multi 10 and E 232E-8/230 Multi 10 product series have 10 functions that can be set on the front of the unit.

### Technique

Fonction	Electronic
Reset Function	Push Button
Tension nominale (U <sub>r</sub> )	240 V AC
Tension d'alimentation	0.85 ... 1.1 V
Maximum Control Current DC	26 mA

Fréquence assignée (f)	50 ... 60 Hz
Maximum Lamp Load	LED Power > 2W 180 W LED Power < 2W 20 W
Power Loss	6 V·A
Puissance Watt	Filament Lamp 2300 W Fluorescent Lamp Compensated 2300 V·A Fluorescent Lamp Shunt Capacitive 1300 V·A Fluorescent Lamp Inductive 2300 V·A Halogen Lamp 2300 W
Minimum Switching Time	0.02/0.05 second [unit of time]
Time Range	0.5 – 20 min. stepless
Appareil	Électronique
Type de charge	2300W Inductive load, $\cos\phi = 0.6/230$ VAC
Switch Type	SteadyLight
Matériau du boîtier	Heat resistant, self-extinguishing thermoplast
Options Provided	Without Switch-Off Warning
Section de câble	Terminal 4 mm <sup>2</sup> Terminal 13 mm <sup>2</sup>
Connection Mode and Capacity	3 or 4 conductor operated automatically
Control Supply Voltage	230 AC V
Contact Material	silver-tin-oxide (AgSnO <sub>2</sub> )
Rated Switching Capacity	16 A 230 V AC
Switch Off Warning Type	Flickering

## Environnement

Température extérieure	-25 ... 50 °C
Statut RoHS	Following EU Directive 2011/65/EU
Informations RoHS	2CDK440004K0202
REACH Declaration	9AKK107492A1907
Informations environnementales	2CDU400020D0201
SCIP	b4b88b52-18ba-4dfe-ad52-6daf0f5148f6 Germany (DE)

## Dimensions

Produit Largeur Net	17.5 mm
Produit Hauteur Net	90 mm
Produit Longueur Net	58 mm
Poids net	0.07 kg

## Commande

Quantité minimum	1 pièce
Emballage Niveau 1 Unités	box 10 pièce
Emballage Niveau 1 Poids	1.05 kg

E-Number (Finland)

3510147

---

## Certificats et Déclarations (Numéro de document)

---

Déclaration de Conformité - CE	2CDK440040D0201
EAC Certificate	9AKK108466A2730
VDE Certificate	9AKK108466A2521

---



---

## Installation

---

Installation Manual	9AKK108466A2386
Instructions et manuels	9AKK108466A2386

---



---

## Popular Downloads

---

Fiche produit, informations techniques	9AKK106930A8017
---	-----------------

---



---

## Classifications

---

ETIM 8	EC000297 - Staircase lighting timer
ETIM 9	EC000297 - Staircase lighting timer
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
DEEE B2C / B2B	Business To Consumer
CN8	8536 49 00
eClass	V11.0 : 27142307

---



---

## Catégories

---

Produits basse tension → Appareillage modulaire et parafoudres → Control and Automation Devices → Staircase Switches

