


IGA 10 V2 IP54 (902 315)

- Lightning-impulse-current-tested insulating enclosure



Figure without obligation



Dimension drawing IGA 10 V2 IP54

Lightning-current-tested insulating enclosure with a max. capacity of ten modules; with grommet flange for 11 EPDM cables (Ø5-30 mm) and three mounted M20 grommet openings with lock nut; ideally suited for series connection.

| Type | IGA 10 V2 IP54 |
|-------------------------|---|
| Part No. | 902 315 |
| Degree of protection | IP 54 |
| Type | lightning-current-tested |
| Type of cover | transparent |
| Colour of enclosure | grey |
| Number of cable entries | 4x for cables Ø5-7mm; 3x for cables Ø7-10 mm; 2x for cables Ø10-14 mm or Ø15-30 mm each; 3x for cables Ø8-13 mm |
| Capacity | 10 modules, DIN 43880 |
| Dimensions (W x H x D) | 200 x 300 x 132 mm |
| Cover | sealable |
| Weight | 1,83 kg |
| Customs tariff number | 85389099 |
| GTIN | 4013364125759 |
| PU | 1 Stk |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.