

PRODUCT-DETAILS

6736/01-884

6736/01-884 Wall sensor for ZigBee Light Link
ZigBee Light Link 2 channel 2gang(s) studio
white matt - 63x63Radio Control



Informations générales

Extension du type de produit	6736/01-884
Code de produit	2CKA006730A0124
EAN	4011395200841
Description courte	6736/01-884 Wall sensor for ZigBee Light Link ZigBee Light Link 2 channel 2gang(s) studio white matt - 63x63Radio Control

Description longue	<p>2gang wall-mounted transmitter independent of mains power supply. For the wireless remote control of other ZigBee Light Link radio components. For saving and calling up 4 light scenes. For dimming 2 light scenes. For combining with/integrating in other systems which operate with the ZigBee Light Link protocol, such as Philips hue. With labelling field. Without enclosed labelling sheet. Compatible lettering software is available at www.busch-jaeger-labelingtool.com. Send/receive frequency: 2.4 GHz. Free-field range: approx. 100 m. Power supply: lithium button cell battery type CR2450 (included in scope of delivery) Battery service life: typically 3 years. Automatic monitoring of battery life. Including fixing plate for mounting on smooth walls or on switch boxes.</p>
--------------------	--

Installation

Instructions et manuels	2CKA000073B9245
-------------------------	-----------------

Technique

Application	ZigBee Light Link
Tension nominale (U _n)	3 V
Auxiliary Voltage AC/DC	3 V AC/DC
Number of Channels	2
Number of Gangs	2
Design Range	63x63 future linear Busch-axcent Busch-axcent pur carat
Norme de transmission	Radio Control
Type de montage	Flush Mounted
Finition de surface	Surface protection: Lacquered Surface finishing: Matt
Label Space Provided	Yes
Type d'encastrement	wall
Model Number	ZigBee Light Link
RAL Number	RAL 9016 - Blanc signalisation
Couleur	studio white matt
Composition chimique de la batterie	Lithium
Type de batterie	Pile bouton
Poids de la batterie	6.2 g
Nombre de batteries	1
Application Function	Electrical Load and Light Control

Environnement

Température de l'air ambiant	Operation -5 ... +45 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CKA200000E6292
REACH Declaration	2CKA309999E9999

Dimensions

Produit Largeur Net	71 mm
Produit Hauteur Net	71 mm
Produit Longueur Net	25 mm
Poids net	62 g

Commande

Quantité minimum	1 pièce
Emballage Niveau 1 Unités	carton 1 pièce
Emballage Niveau 1 Poids	0.12 kg

Code douanier	85389099
Pays d'origine	Germany (DE)

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E1850
-----------------------------------	-----------------

Classifications

ETIM 8	EC000257 - Transmitter/Remote control for domestic switching devices
ETIM 9	EC000257 - Transmitter/Remote control for domestic switching devices
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
DEEE B2C / B2B	Business To Consumer
CN8	8538 90 99
eClass	V11.0 : 27144039

Catégories

Produits basse tension → Wiring Accessories - Light Switch Ranges → Cover Plates (partly incl. Insert) → Electronic Controls

